



Test Report No. 622421-01-1



**MASH TEST 3-21 OF FREE-STANDING-TO-ANCHORED F-SHAPE
PCB TRANSITION SYSTEM WITH VERTICAL ANCHORS ON ASPHALT**

Sponsored by
Roadside Safety Pooled Fund

TEXAS A&M TRANSPORTATION
INSTITUTE PROVING GROUND
Roadside Safety & Physical Security
Texas A&M University System
RELLIS Campus
Building 7091
1254 Avenue A
Bryan, TX 77807



ISO 17025 Laboratory
Testing Certificate # 2821.01

1. Report No. T 1969	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle MASH Test 3-21 of Free-Standing-to-Anchored F-shape PCB Transition System with Vertical Anchors on Asphalt		5. Report Date November 2025	6. Performing Organization Code
7. Author(s) Nauman M. Sheikh, P.E. and Brianna E. Brest van Kempen		8. Performing Organization Report No. TRNo. 622421-01-1	
9. Performing Organization Name and Address Texas A&M Transportation Institute Proving Ground 3135 TAMU, College Station, Texas 77843-3135		10. Work Unit No. (TRAIS)	
		11. Contract or Grant No. Contract T 1969	
12. Sponsoring Agency Name and Address California Department of Transportation Division of Research, Innovation and System Information Roadside Safety Research Group 5900 Folsom Blvd., Sacramento, CA 95819		13. Type of Report and Period Covered Technical Report: June 2025	
		14. Sponsoring Agency Code	
15. Supplementary Notes Name of Contacting Representative: D. Jean Vedenoff			
16. Abstract The purpose of this project was to evaluate the performance of a new free-standing-to-anchored F-shape portable concrete barrier (PCB) transition system. The anchored portion of the PCB system utilized vertical anchors installed in asphalt pavement. The evaluation was conducted in accordance with the safety-performance assessment procedures outlined in <i>the Manual for Assessing Safety Hardware (MASH), Second Edition</i> , published by the American Association of State Highway and Transportation Officials (AASHTO) (1). A full-scale crash test was carried out following MASH Test 3-21 impact conditions, which specify an impact of the transition system by a 5,000-lb pickup truck traveling at 62 mi/h and striking the barrier at an angle of 25 degrees.			
This report provides details of the free-standing-to-anchored F-shape PCB transition system, the crash test procedures and results, and the performance assessment of the transition system in accordance with <i>MASH</i> Test 3-21 evaluation criteria. The new free-standing-to-anchored F-shape PCB transition system met the performance criteria for <i>MASH</i> Test 3-21.			
The optional <i>MASH</i> Test 3-20, involving a small passenger car, was not considered critical for evaluating the transition system and was not conducted. Based on the results of the crash testing, the free-standing-to-anchored F-shape PCB is considered compliant with <i>MASH</i> Test Level 3 criteria.			
17. Key Words Transition System, Barrier Transition, Longitudinal Barrier, Anchored PCB system, Asphalt, Vertical Anchors, Pinned Barrier, Free-Standing Barrier, Pavement		18. Distribution Statement No Restrictions	
19. Security Classification. (of this report) Unclassified	20. Security Classification. (of this page) Unclassified	21. No. of Pages 95	22. Price

MASH Test 3-21 of Free-Standing-to-anchored PCB System on Asphalt

by
Nauman M. Sheikh, P.E.
Senior Research Engineer
Texas A&M Transportation Institute

and

Brianna E. Brest van Kempen
Research Assistant
Texas A&M Transportation Institute

Report No. 622421-01-1
Contract No.: T 1969

Sponsored by the
Roadside Safety Pooled Fund

November 2025

TEXAS A&M TRANSPORTATION INSTITUTE
College Station, Texas 77843-3135

DISCLAIMER

The contents of this report reflect the views of the authors, who are solely responsible for the facts and accuracy of the data and the opinions, findings, and conclusions presented herein. The contents do not necessarily reflect the official views or policies of the Roadside Safety Pooled Fund, The Texas A&M University System, or the Texas A&M Transportation Institute (TTI). This report does not constitute a standard, specification, or regulation. In addition, the above listed agencies/companies assume no liability for its contents or use thereof. The names of specific products or manufacturers listed herein do not imply endorsement of those products or manufacturers.

The results reported herein apply only to the article tested. The full-scale crash test was performed according to TTI Proving Ground quality procedures and American Association of State Highway and Transportation Officials (AASHTO) Manual for Assessing Safety Hardware, Second Edition (*MASH*) guidelines and standards.

The Proving Ground Laboratory within TTI's Roadside Safety and Physical Security Division ("TTI Lab") strives for accuracy and completeness in its crash test reports. On rare occasions, unintentional or inadvertent clerical errors, technical errors, omissions, oversights, or misunderstandings (collectively referred to as "errors") may occur and may not be identified for corrective action prior to the final report being published and issued. If, and when, the TTI Lab discovers an error in a published and issued final report, the TTI Lab will promptly disclose such error to Roadside Safety Pooled Fund, and both parties shall endeavor in good faith to resolve this situation. The TTI Lab will be responsible for correcting the error that occurred in the report, which may be in the form of errata, amendment, replacement sections, or up to and including full reissuance of the report. The cost of correcting an error in the report shall be borne by the TTI Lab. Any such errors or inadvertent delays that occur in connection with the performance of the related testing contract will not constitute a breach of the testing contract.

ACKNOWLEDGEMENTS

This research project was performed under a pooled fund program between the following States and Agencies. The authors acknowledge and appreciate their guidance and assistance.

Roadside Safety Research Pooled Fund Committee Revised April 2024

ALABAMA

Wade Henry, P.E.

Assistant State Design Engineer
Design Bureau, Final Design Division
Alabama Dept. of Transportation
1409 Coliseum Boulevard, T-205
Montgomery, AL 36110
(334) 242-6464
henryw@dot.state.al.us

Stanley (Stan) C. Biddick, P.E.

State Design Engineer
Alabama Dept. of Transportation
1409 Coliseum Boulevard, T-205
Montgomery, AL 36110
(334) 242-6488
biddicks@dot.state.al.us

ALASKA

Mary F. McRae

Assistant State Traffic & Safety
EngineerAlaska Depart. of Transportation &
Public Facilities
3132 Channel Drive
P.O. Box 112500
Juneau, AK 99811-2500
(907) 465-6963
mary.mcrae@alaska.gov

Micheal Hills

Alaska Depart. of Transportation & Public
Facilities
micheal.hills@alaska.gov

CALIFORNIA

Bob Meline, P.E.

Caltrans
Office of Materials and Infrastructure
Division of Research and Innovation
5900 Folsom Blvd
Sacramento, CA 95819
(916) 227-7031
Bob.Meline@dot.ca.gov

John Jewell, P.E.

Senior Crash Testing Engineer
Office of Safety Innovation & Cooperative
Research
(916) 227-5824
John_Jewell@dot.ca.gov

COLORADO

David Kosmiski, P.E.

Miscellaneous (M) Standards Engineer
Division of Project Support, Construction
Engineering Services (CES) Branch
Colorado Dept. of Transportation (CDOT)
2829 W. Howard Pl.
Denver, CO 80204
303-757-9021
david.kosmiski@state.co.us

Andy Pott, P.E.

Senior Bridge Design and Construction
Engineer
Division of Project Support, Staff Bridge
Design and Construction Management
Colorado Dept. of Transportation (CDOT)
4201 E Arkansas Ave, 4th Floor
Denver, CO 80222
303-512-4020
andrew.pott@state.co.us

Shawn Yu, P.E.

Miscellaneous (M) Standards and
Specifications Unit Manager
Division of Project Support, Construction
Engineering Services (CES) Branch
Colorado Dept. of Transportation (CDOT)
4201 E Arkansas Ave, 4th Floor
Denver, CO 80222
303-757-9474
shawn.yu@state.co.us

Amin Fakhimalizad

Assistant Miscellaneous (M) Standards
Engineer
Division of Project Support, Construction
Engineering Services (CES) Branch
Colorado Dept. of Transportation (CDOT)
303-757-9229
amin.fakhimalizad@state.co.us

Man (Steven) Yip

Division of Project Support, Construction
Engineering Services (CES) Branch
Colorado Dept. of Transportation (CDOT)
man.yip@state.co.us

CONNECTICUT**David Kilpatrick**

Transportation Supervising Engineer
State of Connecticut Depart. of
Transportation
2800 Berlin Turnpike
Newington, CT 06131-7546
(806) 594-3288
David.Kilpatrick@ct.gov

Todd Ingarra

todd.ingarra@ct.gov

DELAWARE**Cassidy Blowers**

Construction Resource Engineer
Construction Section
Delaware DOT
(302)760-2336
Cassidy.Blowers@delaware.gov

James Osborne

Traffic Safety Programs Manager
Traffic Operations
Delaware DOT
(302)659-4651
James.Osborne@delaware.gov

FLORIDA**Richard Stepp**

Florida Department of Transportation
Richard.Stepp@dot.state.fl.us

Derwood C. Sheppard, Jr., P.E.

State Roadway Design Engineer
Florida Depart. of Transportation
Roadway Design Office
605 Suwannee Street, MS-32
Tallahassee, FL 32399-0450
(850) 414-4334

Derwood.Sheppard@dot.state.fl.us

IDAHO**Marc Danley, P.E.**

Technical Engineer
(208) 334-8558
Marc.danley@itd.idaho.gov

Kevin Sablan

Design/Traffic Engineer
Idaho Transportation Department
(208) 334-8558
Kevin.sablan@itd.idaho.gov

ILLINOIS**Martha A. Brown, P.E.**

Safety Design Bureau Chief
Bureau of Safety Programs and Engineering
Illinois Depart. of Transportation
2300 Dirksen Parkway, Room 005
Springfield, IL 62764
(217) 785-3034
Martha.A.Brown@illinois.gov

Edgar A. Galofre, MSCE, P.E.

Safety Design Engineer

Bureau of Safety Programs and Engineering
Illinois Department of Transportation
2300 S. Dirksen Parkway, Room 007
Springfield, IL 62764
(217) 558-9089

Edgar.Galofre@illinois.gov

IOWA**Daniel Harness**

Design Bureau – Methods Section
Iowa Department of Transportation
Daniel.Harness@iowadot.us

Chris Poole

State Traffic Engineer
Traffic and Safety Bureau
Iowa Department of Transportation
Chris.Poole@iowadot.us

LOUISIANA**Carl Gaudry**

Bridge Design Manager
Louisiana Department of Transportation and
Development
Bridge & Structural Design Section
P.O. Box 94245
Baton Rouge, LA 70804-9245
(225) 379-1075
Carl.Gaudry@la.gov

Chris Guidry

Assistant Bridge Design Administrator
Louisiana Department of Transportation and
Development
Bridge & Structural Design Section
P.O. Box 94245
Baton Rouge, LA 79084-9245
(225) 379-1328
Chris.Guidry@la.gov

MARYLAND**Philip Brentlinger**

Maryland State Highway Administration
pbrentlinger@mdot.maryland.gov

MASSACHUSETTS**James Danila**

Assistant State Traffic Engineer
Massachusetts Depart. of Transportation
(857) 368-9640
James.danila@state.ma.us

Alex Bardow

Director of Bridges and Structure
Massachusetts Depart. of Transportation
10 Park Plaza, Room 6430
Boston, MA 02116
(857) 368-9430
Alexander.Bardow@state.ma.us

MICHIGAN**Carlos Torres, P.E.**

Roadside Safety Engineer
Geometric Design Unit, Design Division
Michigan Depart. of Transportation
P. O. Box 30050
Lansing, MI 48909
(517) 335-2852
TorresC@michigan.gov

MINNESOTA**Khamsai Yang**

Design Standards Engineer
Office of Project Management and
Technical Support
(612) 322-5601
Khamsai.Yang@state.mn.us

Brian Tang

Assistant Design Standards Engineer
Office of Project Management and
Technical Support
Minnesota Department of Transportation
brian.tang@state.mn.us

MISSOURI**Gidget Koestner**

Policy & Innovations Engineer
Central Office- Design
Missouri Department of Transportation
(573) 751-6905
gidget.koestner@modot.mo.gov

Kirby Woods

Roadside Design Engineer
Missouri Department of Transportation
(573) 472-5333
kirby.woodsjr@modot.mo.gov

NEW MEXICO**Brad Julian**

New Mexico Department of Transportation
Traffic Technical Support Engineer
(505) 469-1405
Brad.Julian@dot.nm.gov

NEVADA**David Fox, P.E.**

Specifications Engineer
Roadway Design Division
Nevada Dept. of Transportation
1263 S. Stewart St.
Carson City, NV 89712
(775) 888-7053
DWFox@dot.nv.gov

Tim Rudnick

Standards and Manuals Supervisor
Roadway Design Division
Nevada Dept. of Transportation
1263 S. Stewart St.
Carson City, NV 89712
(775) 888-7598
TRudnick@dot.nv.gov

OHIO**Don P. Fisher, P.E.**

Ohio Depart. of Transportation
1980 West Broad Street
Mail Stop 1230
Columbus, OH 43223
(614) 387-2614
Don.fisher@dot.ohio.gov

OREGON**Christopher Henson**

Senior Roadside Design Engineer
Oregon Depart. of Transportation
Technical Service Branch
4040 Fairview Industrial Drive, SE
Salem, OR 97302-1142
(503) 986-3561
Christopher.S.Henson@odot.state.or.us

PENNSYLVANIA**James A. Borino, Jr., P.E.**

Chief, Standards and Criteria Unit
Highway Design and Technology Division
Pennsylvania DOT
(717) 612-4791
jborino@pa.gov

Evan Pursel

Senior Civil Engineer
Highway Design and Technology Division
Pennsylvania DOT
(717) 705-8535
epursel@pa.gov

Nina Ertel

Project Development Engineer
Highway Design and Technology Division
Pennsylvania DOT
(717) 425-7679
nertel@pa.gov

TENNESSEE**Laura Chandler**

Engineering Production Support Manager
Engineering Division
Tennessee Dept. of Transportation
(615) 253-4769
Laura.Chandler@tn.gov

Ali Hangul M.S., P.E

State Standards Transportation Engineer
Engineering Production Support,
Engineering Division
Tennessee Dept. of Transportation
(615) 741-0840
Ali.Hangul@tn.gov

TEXAS

Chris Lindsey

Transportation Engineer
Design Division
Texas Department of Transportation
125 East 11th Street
Austin, TX 78701-2483
(512) 416-2750
Christopher.Lindsey@txdot.gov

Taya Retterer

TxDOT Bridge Standards Engineer
Bridge Division
Texas Department of Transportation
(512) 993-0330
Taya.Retterer@txdot.gov

Wade Odell

Research Project Manager
Research & Technology Implementation
Division
Texas Department of Transportation
(512) 416-4737
wade.odell@txdot.gov

UTAH

Clint McCleery

Barrier and Attenuation Specialist
Traffic and Safety Operations
Utah Department of Transportation
(801)712-8685
cmccleery@utah.gov

WASHINGTON

Tim Moeckel

Roadside Safety Engineer
Washington State Department of
Transportation
Development Division
P.O. Box 47329
Olympia, WA 98504-7246
(360) 704-6377
moecket@wsdot.wa.gov

Mustafa Mohamedali

Research Manager/Engineering
Transportation Safety & System Analysis
Research & Library Services
(360) 704-6307
mohamem@wsdot.wa.gov

Kevin Burch

Policy Support Engineer
Washington State Department of
Transportation
Development Division
burchk@wsdot.wa.gov

WEST VIRGINIA

Donna J. Hardy, P.E.

Mobility, ITS & Safety Engineer
West Virginia Depart. of
Transportation – Traffic Engineering
Building 5, Room A-550
1900 Kanawha Blvd E.
Charleston, WV 25305-0430
(304) 414-7338
Donna.J.Hardy@wv.gov

Ted Whitmore

Traffic Services Engineer
Traffic Engineering
WV Division of Highways
(304)414-7373
Ted.J.Whitmore@wv.gov

WISCONSIN

Erik Emerson, P.E.

Standards Development Engineer –
Roadside Design
Wisconsin Department of Transportation
Bureau of Project Development
4802 Sheboygan Avenue, Room 651
P. O. Box 7916
Madison, WI 53707-7916
(608) 266-2842
Erik.Emerson@wi.gov

CANADA – ONTARIO

Kenneth Shannon, P. Eng.

Senior Engineer, Highway Design (A)
Ontario Ministry of Transportation
301 St. Paul Street
St. Catharines, ON L2R 7R4
CANADA
(904) 704-3106
Kenneth.Shannon@ontario.ca

FEDERAL HIGHWAY

ADMINISTRATION (FHWA)

Website: safety.fhwa.dot.gov

Eduardo Arispe

Research Highway Safety Specialist
U.S. Department of Transportation
Federal Highway Administration
Turner-Fairbank Highway Research Center
Mail Code: HRDS-10
6300 Georgetown Pike
McLean, VA 22101
(202) 493-3291
Eduardo.arispe@dot.gov

Richard B. (Dick) Albin, P.E.

Senior Safety Engineer
Office of Innovation Implementation, Safety
& Design Team
(303) 550-8804
Dick.Albin@dot.gov

Paul LaFleur, P.E.

Safety Design Team - Roadway Departure
Program Manager
FHWA Office of Safety
U.S. Department of Transportation
(515) 233-7308
paul.lafleur@dot.gov

Christine Black

Highway Safety Engineer
Central Federal Lands Highway Division
12300 West Dakota Ave.
Lakewood, CO 80228
(720) 963-3662
Christine.black@dot.gov

Isbel Ramos-Reyes

Lead Safety and Transportation Operations
Engineer
Eastern Federal Lands Highway Division
(703) 948-1442
isbel.ramos-reyes@dot.gov

TEXAS A&M TRANSPORTATION INSTITUTE (TTI)

Website: tti.tamu.edu
www.roadsidepooledfund.org

D. Lance Bullard, Jr., P.E.

Senior Research Engineer
Roadside Safety & Physical Security Div.
Texas A&M Transportation Institute
3135 TAMU
College Station, TX 77843-3135
(979) 317-2855
L-Bullard@tti.tamu.edu

Roger P. Bligh, Ph.D., P.E.

Senior Research Engineer
Roadside Safety and Physical Security
Division
(979) 317-2703
R-Bligh@tti.tamu.edu

Nauman Sheikh, P.E.

Research Engineer
Roadside Safety and Physical Security
Texas A&M Transportation Institute
(979) 317-2703
n-sheikh@tti.tamu.edu

Ariel Sheil

Research Assistant
Roadside Safety and Physical Security
Texas A&M Transportation Institute
(979) 317-2250
A-Sheil@tti.tamu.edu

REPORT AUTHORIZATION

REPORT REVIEWED BY:



Glenn Schroeder
Research Specialist
Drafting & Reporting



Ken Reeves
Research Specialist
Electronics Instrumentation




Adam Mayer
Research Specialist
Construction



Richard Badillo
Research Specialist
Photographic Instrumentation



Robert Kocman
Research Specialist
Mechanical Instrumentation



Brianna E. Brest van Kempen
Research Assistant
Research Evaluation and Reporting



Bill L. Griffith
Research Specialist
Quality Manager



William J. L. Schroeder
Research Engineering Associate
Research Evaluation and Reporting



Matthew N. Robinson
Research Specialist
Test Facility Manager & Technical
Manager



Nauman M. Sheikh, P.E.
Senior Research Engineer
Research Supervisor

REVISION LOG

TABLE OF CONTENTS

	Page
Chapter 1. Introduction	1
Chapter 2. System Details	3
2.1. Test Article and Installation Details	3
2.2. Design Modifications during Tests.....	3
2.3. Material Specifications.....	8
Chapter 3. Test Requirements and Evaluation Criteria	9
3.1. Crash Test Performed/Matrix.....	9
3.2. Evaluation Criteria	9
Chapter 4. Test Conditions	11
4.1. Test Facility	11
4.2. Vehicle Tow and Guidance System	11
4.3. Data Acquisition Systems	12
4.3.1. Vehicle Instrumentation and Data Processing.....	12
4.3.2. Anthropomorphic Dummy Instrumentation.....	13
4.3.3. Photographic Instrumentation Data Processing.....	13
Chapter 5. <i>MASH</i> Test 3-21 (Crash Test 622421-01-1)	15
5.1. Critical Impact Point Location.....	15
5.2. Test Vehicle Details Prior to Impact.....	17
5.3. Test Description.....	19
5.3.1. Weather Conditions	19
5.3.2. Test Events.....	19
5.4. Test Actual Impact Conditions.....	19
5.5. Damage to Test Installation	20
5.6. Damage to Test Vehicle	27
5.7. Occupant Risk Factors	30
5.8. Test Summary	30
Chapter 6. Summary and Conclusions	33
6.1. Implementation	33
References	35
Appendix A. Details of free-standing-to-anchored PCB transition system	37
Appendix B. Supporting Certification Documents	49
Appendix C. <i>MASH</i> Test 3-21 (Test 622421-01-1).....	83
C.1. Vehicle Properties and Information.....	83
C.2. Sequential Photographs	86
C.3. Vehicle Angular Displacements	89
C.4. Vehicle Accelerations	91

LIST OF FIGURES

	Page
Figure 2.1. Details of the Free-Standing-to-Anchored PCB Transition System.....	4
Figure 2.2. Free-Standing-to-Anchored PCB Transition System Prior to Testing.....	5
Figure 2.3. Downstream In-Line View of the Free-Standing-to-Anchored PCB Transition System Prior to Testing.....	5
Figure 2.4. Closeup View of Joint Between Barriers 7 and 8 Prior to Testing.....	6
Figure 2.5. Upstream End of the Test Installation Prior to Testing.....	6
Figure 2.6. Field Side View of the Transition System at Joint Between Segments 9 and 10 Prior to Testing.....	7
Figure 2.7. Closeup View of Installed Anchor Pin Prior to Testing.	7
Figure 5.1. Target CIP for <i>MASH</i> Test 3-21 on Free-Standing-to-Anchored PCB Transition System.....	15
Figure 5.2. Front View of Test Vehicle Impact Location for Test 622421-01-1.	16
Figure 5.3. Rear View of Test Vehicle Impact Location for Test 622421-01-1.....	16
Figure 5.4. Impact Side of Test Vehicle before Test 622421-01-1.	18
Figure 5.5. Opposite Impact Side of Test Vehicle before Test 622421-01-1.	18
Figure 5.6. Downstream In-Line View of the Transition System after Test 622421-01-1.	23
Figure 5.7. Upstream View of the Transition System after Test 622421-01-1.....	24
Figure 5.8. Impact-Side View of Barrier Segment 9 after Test 622421-01-1.....	24
Figure 5.9. Non-Impact-Side View of Barrier Segment 9 after Test 622421-01-1.....	25
Figure 5.10. Upstream Barrier End after Test 622421-01-1.	25
Figure 5.11. Anchoring Pins, Connection Pin, and Asphalt Damage at Joint between Barrier Segments 8 and 9 Post-Disassembly after Test 622421-01-1.	26
Figure 5.12. Impact Side of Test Vehicle after Test 622421-01-1.....	27
Figure 5.13. Rear Impact Side of Test Vehicle after Test 622421-01-1.	27
Figure 5.14. Overall Interior of Test Vehicle after Test 622421-01-1.	28
Figure 5.15. Interior of Test Vehicle on Impact Side after Test 622421-01-1.....	28
Figure 5.16. Summary of Results for <i>MASH</i> Test 3-21 on Free-Standing-to-Anchored F- shape PCB Transition system.	31
Figure C.1. Vehicle Properties for Test 622421-01-1.....	83
Figure C.2. Exterior Crush Measurements for Test 622421-01-1.....	84
Figure C.3. Occupant Compartment Measurements for Test 622421-01-1.	85
Figure C.4. Sequential Photographs for Test 622421-01-1 (Overhead View).	86
Figure C.5. Sequential Photographs for Test 622421-01-1 (Downstream In-line View).	87
Figure C.6. Sequential Photographs for Test 622421-01-1 (Upstream Field Side Oblique View).	88
Figure C.7. Vehicle Angular Displacements for Test 622421-01-1.....	90

Figure C.8. Vehicle Longitudinal Accelerometer Trace for Test 622421-01-1 (Accelerometer Located at Center of Gravity).....	92
Figure C.9. Vehicle Lateral Accelerometer Trace for Test 622421-01-1 (Accelerometer Located at Center of Gravity).....	93
Figure C.10. Vehicle Vertical Accelerometer Trace for Test 622421-01-1 (Accelerometer Located at Center of Gravity).....	94

LIST OF TABLES

	Page
Table 2.1. Concrete Strength.....	8
Table 3.1. Test Conditions and Evaluation Criteria Specified for <i>MASH TEST 3-21</i> Longitudinal Barrier.....	9
Table 3.2. Evaluation Criteria Required for <i>MASH</i> Testing.....	10
Table 5.1. Vehicle Measurements for Test 622421-01-1.....	17
Table 5.2. Weather Conditions for Test 622421-01-1.....	19
Table 5.3. Events during Test 622421-01-1.....	19
Table 5.4. Impact Conditions for <i>MASH TEST 3-21</i> , Crash Test 622421-01-1.....	20
Table 5.5. Exit Parameters for <i>MASH TEST 3-21</i> , Crash Test 622421-01-1.....	20
Table 5.6. Barrier Segment Displacements at Joint Locations for Test 622421-01-1..	22
Table 5.7. Deflections and Working Width for Test 622421-01-1.....	23
Table 5.8. Occupant Compartment Deformation 622421-01-1.....	29
Table 5.9. Exterior Vehicle Damage 622421-01-1.....	29
Table 5.10. Occupant Risk Factors for Test 622421-01-1.....	30
Table 6.1. Assessment Summary for <i>MASH TEST 3-21</i> Tests on free-standing-to- anchored PCB transition system.....	33

SI* (MODERN METRIC) CONVERSION FACTORS				
APPROXIMATE CONVERSIONS TO SI UNITS				
Symbol	When You Know	Multiply By	To Find	Symbol
		LENGTH		
in	inches	25.4	millimeters	mm
ft	feet	0.305	meters	m
yd	yards	0.914	meters	m
mi	miles	1.61	kilometers	km
		AREA		
in ²	square inches	645.2	square millimeters	mm ²
ft ²	square feet	0.093	square meters	m ²
yd ²	square yards	0.836	square meters	m ²
ac	acres	0.405	hectares	ha
mi ²	square miles	2.59	square kilometers	km ²
		VOLUME		
fl oz	fluid ounces	29.57	milliliters	mL
gal	gallons	3.785	liters	L
ft ³	cubic feet	0.028	cubic meters	m ³
yd ³	cubic yards	0.765	cubic meters	m ³
NOTE: volumes greater than 1000L shall be shown in m ³				
		MASS		
oz	ounces	28.35	grams	g
lb	pounds	0.454	kilograms	kg
T	short tons (2000 lb)	0.907	megagrams (or metric ton")	Mg (or "t")
		TEMPERATURE (exact degrees)		
°F	Fahrenheit	5(F-32)/9 or (F-32)/1.8	Celsius	°C
		FORCE and PRESSURE or STRESS		
lbf	poundforce	4.45	newtons	N
lbf/in ²	poundforce per square inch	6.89	kilopascals	kPa
APPROXIMATE CONVERSIONS FROM SI UNITS				
Symbol	When You Know	Multiply By	To Find	Symbol
		LENGTH		
mm	millimeters	0.039	inches	in
m	meters	3.28	feet	ft
m	meters	1.09	yards	yd
km	kilometers	0.621	miles	mi
		AREA		
mm ²	square millimeters	0.0016	square inches	in ²
m ²	square meters	10.764	square feet	ft ²
m ²	square meters	1.195	square yards	yd ²
ha	hectares	2.47	acres	ac
km ²	Square kilometers	0.386	square miles	mi ²
		VOLUME		
mL	milliliters	0.034	fluid ounces	oz
L	liters	0.264	gallons	gal
m ³	cubic meters	35.314	cubic feet	ft ³
m ³	cubic meters	1.307	cubic yards	yd ³
		MASS		
g	grams	0.035	ounces	oz
kg	kilograms	2.202	pounds	lb
Mg (or "t")	megagrams (or "metric ton")	1.103	short tons (2000lb)	T
		TEMPERATURE (exact degrees)		
°C	Celsius	1.8C+32	Fahrenheit	°F
		FORCE and PRESSURE or STRESS		
N	newtons	0.225	poundforce	lbf
kPa	kilopascals	0.145	poundforce per square inch	lb/in ²

*SI is the symbol for the International System of Units

CHAPTER 1.

INTRODUCTION

The objective of this project was to evaluate the performance of a newly developed free-standing-to-anchored F-shape portable concrete barrier (PCB) transition system. This transition system was designed to connect California Department of Transportation's (Caltrans) free-standing F-shape PCB barrier to anchored F-shape PCB barrier. The anchored portion of the system incorporated vertical anchors installed in asphalt pavement. The anchored F-shape PCB system with vertical anchors installed in asphalt pavement was previously crash tested under MASH Test Level 3 (TL-3) conditions (2).

The evaluation of the new transition system was performed in accordance with the safety-performance assessment procedures outlined in the *Manual for Assessing Safety Hardware (MASH), Second Edition*, published by the American Association of State Highway and Transportation Officials (AASHTO) (1). A full-scale crash test was conducted following the MASH Test 3-21 impact conditions, which specify a 5,000-lb pickup truck impacting the barrier at a speed of 62 mi/h and an angle of 25 degrees.

Details of the transition system design are presented in Chapter 2. Chapters 3 and 4 provide details of the MASH evaluation criteria and the testing procedures. Test results are provided in Chapter 5. Summary and conclusions from the testing performed under this project are provided in Chapter 6.

CHAPTER 2.

SYSTEM DETAILS

2.1. TEST ARTICLE AND INSTALLATION DETAILS

The installation was 157 feet long, comprised of thirteen 12-ft. long F-shape “pin-and-loop” reinforced concrete barrier segments. The barrier segments were 9-1/2 inches wide at top, 24 inches wide at bottom, and 32 inches tall, and connected to each other with 1-inch diameter connection pins. Barrier segments 1-8 were placed on compacted 2-inch-thick asphalt that was constructed over 6-inch-thick crushed limestone base. Barrier segments 9-13 were placed on compacted 4-inch-thick asphalt that was constructed over 12-inch-thick crushed limestone base.


All barrier segments were fabricated with six slots for hosting anchor pins, three on each side of the barrier. Barrier segments 1-8 were free-standing, i.e., no anchor pins were installed to restrict movement of these barrier segments. Barrier segment 9 was secured to the asphalt with two anchor pins. These pins were installed in the two downstream end slots, one on each side of the barrier segment. Barrier segments 10-13 were secured to the asphalt with four anchor pins each. Two of these anchor pins were in the upstream end and two in the downstream end slots of each barrier segment. No pins were installed in the center slots of any of the barrier segments.

The anchor pins were 1-1/2 inches in diameter and were fabricated with ASTM A36 steel. The pins were 36 inches long, inclusive of a 2-inch tip. A 3-inch x 3-inch x 1/2-inch ASTM A36 plate washer was welded to the top of the anchor pins. To facilitate anchor pin installation, 1-3/4-inch pilot holes were drilled through the asphalt and the underlying soil prior to driving in the pins.

Figure 2.1 presents the overall information on the free-standing-to-anchored PCB transition system, and Figure 2.2 thru Figure 2.7 provide photographs of the installation. Appendix A provides further details on the free-standing-to-anchored PCB transition system. Drawings were provided by the Texas A&M Transportation Institute (TTI) Proving Ground, and construction of the barriers were performed by Summit Precast Concrete, anchor pin construction was done by Custom Fabricators and Repairs Inc., asphalt pad was constructed by Brazos Paving Industries, and TTI Proving Ground personnel assembled the test installation.

2.2. DESIGN MODIFICATIONS DURING TESTS

No modifications were made to the installation during the testing phase.



1a. Place Barriers and insert Connection Pins. Drill Ø1-3/4" holes through asphalt with masonry bit and rotary percussion drill and insert Anchor Pins at Barriers 9 - 13, two at Barrier 9 and four at Barriers 10-13 at end locations (center anchor locations not used; see Detail View).

1b. Total installation length of 157'-0" may vary if space between barriers is more or less than 1 inch.

 Project #622421 PCB Anchored Transition	Roadside Safety and Physical Security Division - Proving Ground 2025-02-27
Drawn by GES	Scale 1:200

Sheet 1 of 10 Test Installation

Figure 2.1. Details of the Free-Standing-to-Anchored PCB Transition System.



Figure 2.2. Free-Standing-to-Anchored PCB Transition System Prior to Testing.



Figure 2.3. Downstream In-Line View of the Free-Standing-to-Anchored PCB Transition System Prior to Testing.



Figure 2.4. Closeup View of Joint Between Barriers 7 and 8 Prior to Testing.



Figure 2.5. Upstream End of the Test Installation Prior to Testing.



Figure 2.6. Field Side View of the Transition System at Joint Between Segments 9 and 10 Prior to Testing.



Figure 2.7. Closeup View of Installed Anchor Pin Prior to Testing.

2.3. MATERIAL SPECIFICATIONS

Appendix B provides material certification documents for the materials used to install/construct the free-standing-to-anchored PCB transition system. Table 2.1 shows the compressive strengths of the concrete from core samples which were taken after the test.

Table 2.1. Concrete Strength.

Location	Design Strength (psi)	Avg. Strength (psi)
Barrier 8	4000	5800
Barrier 9	4000	6070

CHAPTER 3.

TEST REQUIREMENTS AND EVALUATION CRITERIA

3.1. CRASH TEST PERFORMED/MATRIX

Table 3.1 shows the test conditions and evaluation criteria for *MASH TEST 3-21* for Longitudinal Barrier.

Table 3.1. Test Conditions and Evaluation Criteria Specified for *MASH TEST 3-21* Longitudinal Barrier.

Test Designation	Test Vehicle	Impact Speed (mi/h)	Impact Angle (°)	Evaluation Criteria
3-21	2270P	62	25	A, D, F, H, I

The crash tests and data analysis procedures were in accordance with guidelines presented in *MASH*. Chapter 4 presents brief descriptions of these procedures.

3.2. EVALUATION CRITERIA

The appropriate safety evaluation criteria from Tables 2-2 and 5-1 of *MASH* were used to evaluate the crash test reported herein. Table 3.1 lists the test conditions and evaluation criteria required for *MASH TEST 3-21*. Table 3.2 provides detailed information on the evaluation criteria.

Table 3.2. Evaluation Criteria Required for *MASH* Testing.

Evaluation Factors	Evaluation Criteria
A.	Test article should contain and redirect the vehicle or bring the vehicle to a controlled stop; the vehicle should not penetrate, underride, or override the installation although controlled lateral deflection of the test article is acceptable.
D.	Detached elements, fragments, or other debris from the test article should not penetrate or show potential for penetrating the occupant compartment, or present undue hazard to other traffic, pedestrians, or personnel in a work zone. Deformations of, or intrusions into, the occupant compartment should not exceed limits set forth in Section 5.2.2 and Appendix E of <i>MASH</i> .
F.	The vehicle should remain upright during and after collision. The maximum roll and pitch angles are not to exceed 75 degrees.
H.	Occupant impact velocities (OIV) should satisfy the following limits: Preferred value of 30 ft/s, or maximum allowable value of 40 ft/s.
I.	The occupant ridedown accelerations should satisfy the following: Preferred value of 15.0 g, or maximum allowable value of 20.49 g.

CHAPTER 4.

TEST CONDITIONS

4.1. TEST FACILITY

The full-scale crash test reported herein was performed at the TTI Proving Ground, an International Standards Organization (ISO)/International Electrotechnical Commission (IEC) 17025-accredited laboratory with American Association for Laboratory Accreditation (A2LA) Mechanical Testing Certificate 2821.01. The full-scale crash test was performed according to TTI Proving Ground quality procedures, as well as *MASH* guidelines and standards.

The test facilities of the TTI Proving Ground are located on The Texas A&M University System RELLIS Campus, which consists of a 2000-acre complex of research and training facilities situated 10 mi northwest of the flagship campus of Texas A&M University. The site, formerly a United States Army Air Corps base, has large expanses of concrete runways and parking aprons well suited for experimental research and testing in the areas of vehicle performance and handling, vehicle-roadway interaction, highway pavement durability and efficacy, and roadside safety hardware and perimeter protective device evaluation. The sites selected for construction and testing are along the edge of an out-of-service apron. The apron consists of an unreinforced jointed-concrete pavement comprised of 12.5-ft × 15-ft blocks that are nominally 6 inches thick. The apron was built in 1942, and the joints have some displacement but are otherwise flat and level.

4.2. VEHICLE TOW AND GUIDANCE SYSTEM

The 2270P test vehicle was towed into the test installation using a steel cable guidance and reverse tow system. A steel cable for guiding the test vehicle was tensioned along the path, anchored at each end, and threaded through an attachment to the front wheel of the test vehicle. An additional steel cable was connected to the test vehicle, passed around a pulley near the impact point and through a pulley on the tow vehicle, and then anchored to the ground such that the tow vehicle moved away from the test site. A 2:1 speed ratio between the test and tow-vehicle existed with this system. Just prior to impact with the installation, the test vehicle was released and moved unrestrained. The vehicle remained freewheeling (i.e., no steering or braking inputs were applied) until it cleared the immediate area of the test site.

4.3. DATA ACQUISITION SYSTEMS

4.3.1. Vehicle Instrumentation and Data Processing

The test vehicle was instrumented with a self-contained onboard data acquisition system. The signal conditioning and acquisition system is a multi-channel data acquisition system (DAS) produced by Diversified Technical Systems Inc. The accelerometers, which measure the x, y, and z axis of vehicle acceleration, are strain gauge type with linear millivolt output proportional to acceleration. Angular rate sensors, measuring vehicle roll, pitch, and yaw rates, are ultra-small, solid-state units designed for crash test service. The data acquisition hardware and software conform to the *MASH* recommended version of SAE J211, Instrumentation for Impact Test. Each of the channels can provide precision amplification, scaling, and filtering based on transducer specifications and calibrations. During the test, data are recorded from each channel at a rate of 10,000 samples per second with a resolution of one part in 65,536. Once data are recorded, internal batteries back these up inside the unit in case the primary battery cable is severed. Initial contact of the pressure switch on the vehicle bumper provides a time zero mark and initiates the recording process. After each test, the data are downloaded from the DAS unit into a laptop computer at the test site. The Test Risk Assessment Program (TRAP) software then processes the raw data to produce detailed reports of the test results.

Each DAS is returned to the factory annually for complete recalibration and to ensure that all instrumentation used in the vehicle conforms to the specifications outlined by SAE J211. All accelerometers are calibrated annually by means of an ENDEVCO® 2901 precision primary vibration standard. This standard and its support instruments are checked annually and receive a calibration traceable to the International System of Units (SI). Measurement Uncertainties have been determined for critical parameters involved in this testing and are available upon request by the sponsor.

TRAP uses the DAS-captured data to compute the occupant to vehicle contact impact velocities, time of occupant to vehicle contact after vehicle impact, and highest 10-millisecond (ms) average ridedown acceleration. TRAP calculates change in vehicle velocity at the end of a given impulse period. In addition, maximum average accelerations over 50-ms intervals in each of the three directions are computed. For reporting purposes, the data from the vehicle-mounted accelerometers are filtered with an SAE Class 180-Hz low-pass digital filter, and acceleration versus time curves for the longitudinal, lateral, and vertical directions are plotted using TRAP.

TRAP uses the data from the yaw, pitch, and roll rate transducers to compute angular displacement in degrees at 0.0001-s intervals, and then plots yaw, pitch, and roll versus time. These displacements are in reference to the vehicle-fixed coordinate system with the initial position and orientation being initial impact.

4.3.2. Anthropomorphic Dummy Instrumentation

According to *MASH*, use of a dummy in the 2270P vehicle is optional, and no dummy was used in the test.

4.3.3. Photographic Instrumentation Data Processing

Photographic coverage of the test included 3 digital high-speed cameras:

- One placed overhead with a field of view perpendicular to the ground and directly over the impact point.
- One placed with a field of view parallel to and aligned with the installation at the downstream end.
- One placed at an oblique angle upstream from the installation on the impact side.

A flashbulb on the impacting vehicle was activated by a pressure-sensitive tape switch to indicate the instant of contact with the free-standing-to-anchored PCB transition system. The flashbulb was visible from each camera. The video files from these digital high-speed cameras were analyzed to observe phenomena occurring during the collision and to obtain time-event, displacement, and angular data. A digital camera recorded and documented conditions of each test vehicle and the installation before and after the test.

CHAPTER 5.

MASH TEST 3-21 (CRASH TEST 622421-01-1)

5.1. CRITICAL IMPACT POINT LOCATION

The Critical Impact Point (CIP) for Test 3-21 was determined using finite element modeling and simulation and was 195.6 inches [16.3 feet] upstream from the centerline of the joint between barrier segments 9 and 10. Figure 5.1 shows the target CIP for test 622421-01-1. The target impact angle was 25 degrees in accordance with MASH Test 3-21 evaluation criteria. Figure 5.2 and Figure 5.3 depict the vehicle at the CIP prior to test 622421-01-1.




Figure 5.1. Target CIP for MASH Test 3-21 on Free-Standing-to-Anchored PCB Transition System.



Figure 5.2. Front View of Test Vehicle Impact Location for Test 622421-01-1.



Figure 5.3. Rear View of Test Vehicle Impact Location for Test 622421-01-1.

5.2. TEST VEHICLE DETAILS PRIOR TO IMPACT

Table 5.1 shows test vehicle measurements. Figure 5.4 and Figure 5.5 show the 2019 RAM 1500 used for the crash test. Figure C.1 in Appendix C.1 gives additional dimensions and information on the vehicle.

Table 5.1. Vehicle Measurements for Test 622421-01-1.

Test Parameter	Specification	Tolerance	Measured
Dummy Mass (if applicable) ^a (lb)	165	N/A	N/A
Inertial Mass (lb)	5000	±110	5006
Gross Static ^a Mass (lb)	5000	±110	5006
Wheelbase (inches)	148	±12	140.5
Front Overhang (inches)	39	±3	40.3
Overall Length (inches)	237	±13	229.0
Overall Width (inches)	78	±2	78.5
Hood Height (inches)	43	±4	46.0
Track Width ^b (inches)	67	±1.5	68.3
CG aft of Front Axle ^c (inches)	63	±4	59.4
CG above Ground ^{c,d} (inches)	≥28	N/A	28.3

Note: N/A = not applicable; CG = center of gravity.

^a If a dummy is used, the gross static vehicle mass should be increased by the mass of the dummy.

^b Average of front and rear axles.

^c For test inertial mass.

^d 2270P vehicle must meet minimum CG height requirement.



Figure 5.4. Impact Side of Test Vehicle before Test 622421-01-1.



Figure 5.5. Opposite Impact Side of Test Vehicle before Test 622421-01-1.

5.3. TEST DESCRIPTION

5.3.1. Weather Conditions

Table 5.2 provides the weather conditions for Test 622421-01-1. Values for wind direction and vehicle travel are in reference to the degrees on a compass, with North being 0 degrees.

Table 5.2. Weather Conditions for Test 622421-01-1.

Date of Test	6/25/2025
Wind Speed	7 mi/h
Wind Direction	156°
Temperature	85°F
Relative Humidity	80 %
Vehicle Traveling	325°

5.3.2. Test Events

Table 5.3 lists events that occurred during Test 622421-01-1. Figures in Appendix C.2 present sequential photographs during the test.

Table 5.3. Events during Test 622421-01-1.

Time (seconds)	Events
0.0000	Vehicle impacted the installation
0.0310	Vehicle began to redirect
0.0350	Barrier segment 8 began to move toward non-impact-side
0.0840	Front passenger-side tire lifted above the ground
0.1390	Barrier segment 9 began to crack on the non-impact-side
0.2130	Rear passenger-side tire lifted above the ground
0.2320	Vehicle was parallel with the installation
0.4540	Vehicle exited the installation at 45.4 mi/h with a heading of 16.6 degrees and a trajectory of 11.9 degrees

5.4. TEST ACTUAL IMPACT CONDITIONS

Table 5.4 lists details of the impact conditions for this test and Table 5.5 lists the exit parameters.

Table 5.4. Impact Conditions for *MASH TEST 3-21*, Crash Test 622421-01-1.

Test Parameter	Specification	Tolerance	Measured
Impact Speed (mi/h)	62	± 2.5	63.0
Impact Angle (°)	25	± 1.5	25.5
Impact Severity (kip-ft)	106	≥ 106	123.1
Impact Location	195.6 inches upstream from the centerline of the joint between barrier segments 9 and 10	± 1 foot (12 inches)	199.8 inches upstream from the centerline of the joint between barrier segments 9 and 10

Table 5.5. Exit Parameters for *MASH TEST 3-21*, Crash Test 622421-01-1.

Exit Parameter	Measured
Speed	45.4 mi/h
Trajectory	11.9°
Heading	16.6°
Brakes applied post impact	Not applied
Vehicle at rest position	178 ft downstream of impact point 27 ft to the impact side of the barrier
Comments:	Vehicle remained upright and stable. The vehicle met the exit box criteria ^a by crossing the exit box 52 feet downstream from loss of contact.

^aPer the *MASH* guidelines in Section 5.2.3, the exit box for the 2270P used in this test was 16.8 ft toward the impact side as measured from the impact side toe of the barrier and 32.8 ft downstream from loss of contact.

5.5. DAMAGE TO TEST INSTALLATION

Table 5.6 describes the displacement of the joints between the barrier segments of the transition system. Table 5.7 provides the deflection and working width of the transition system. Figure 5.6 through Figure 5.9 show the damage to the transition system.

There was spalling at the base of the joint between barrier segments 8 and 9 on the impact side. There was a significant crack on the non-impact side of barrier segment 8. On barrier segment 9, the downstream impact side face of the barrier segment was raised 2.3 inches from grade, with the anchor pin raised 4.5 inches above the top surface of the pin slot. There were two major cracks and other spalling on barrier segment 9 (Figure 5.8). Both cracks were through the entire cross-section of the barrier segment, exposing rebar on the non-impact-side with major spalling (Figure 5.9). Barrier segments 8 and 9 did not lose continuity despite the concrete damage. On the upstream end of the test installation, barrier segment 1 was displaced 2 inches in the downstream direction (Figure 5.10).

On barrier segment 10 the upstream impact side anchor pin was raised 0.3 inches from grade, and the downstream impact side anchor pin was raised 2 inches. On barrier segment 11 the upstream impact-side anchor pin was raised 0.3 inches, and the downstream impact side anchor pin was raised 0.4 inches. Barriers 12 and 13 had no movement.

None of the barrier connection loops were broken. There were some deformation of the anchoring pins. Figure 5.11 shows the anchoring pins, the connection pin, and the extent of the damage to the underlying pavement at the joint of maximum barrier deflection (between barrier segments 8 and 9 after post-test disassembly of the transition system).

Table 5.6. Barrier Segment Displacements at Joint Locations for Test 622421-01-1.

Joint at Barrier Segments	Joint Displacement (in inches)	Comments
1 (u/s end of installation)	2 d/s, 0.5 i/s	----
1/2	2.5 d/s, 0.5 i/s	----
2/3	2 d/s, 0.5 i/s	----
3/4	2 d/s, 0.5 i/s	----
4/5	2 d/s	----
5/6	2 d/s, 0.5 i/s	----
6/7	2.5 d/s, 2 i/s	3-inch gap on the i/s at the top of barrier, 1.7 inches on the n/s
7/8	11 n/s, 1.2 d/s	1.2 inches gap on the i/s at top of barrier, 2.5 inches n/s
8/9	26.5 d/s, 1 d/s	1.8 inches gap on the i/s at the top of barrier, 3.3 inches n/s
9/10	3 i/s, 3 u/s	Barrier segment 10 pin raised 0.3 inches on i/s

Note: u/s = upstream; d/s = downstream; i/s = impact-side; n/s = non-impact side

Table 5.7. Deflections and Working Width for Test 622421-01-1.

Test Parameter	Measured
Permanent Deflection and Location	26.5 inches toward non-impact side at the joint between barrier segments 8 and 9
Dynamic Deflection	30.4 inches toward non-impact side at the joint between barrier segments 8 and 9
Working Width ^a and Height	51.3 inches, at a height of 3.0 inches at joint between barrier segments 8 and 9

^a Per *MASH*, "The working width is the maximum dynamic lateral position of any major part of the system or vehicle. These measurements are all relative to the pre-impact traffic face of the test article." In other words, working width is the total barrier width plus the maximum dynamic intrusion of any portion of the barrier or test vehicle past the impact side edge of the barrier.



Figure 5.6. Downstream In-Line View of the Transition System after Test 622421-01-1.



Figure 5.7. Upstream View of the Transition System after Test 622421-01-1.



Figure 5.8. Impact-Side View of Barrier Segment 9 after Test 622421-01-1.



Figure 5.9. Non-Impact-Side View of Barrier Segment 9 after Test 622421-01-1.



Figure 5.10. Upstream Barrier End after Test 622421-01-1.



Figure 5.11. Anchoring Pins, Connection Pin, and Asphalt Damage at Joint between Barrier Segments 8 and 9 Post-Disassembly after Test 622421-01-1.

5.6. DAMAGE TO TEST VEHICLE

Figure 5.12 and Figure 5.13 show the damage sustained by the vehicle. Figure 5.14 and Figure 5.15 show the interior of the test vehicle. Table 5.8 and Table 5.9 provide details on the occupant compartment deformation and exterior vehicle damage, respectively. Figure C.2 and Figure C.3 in Appendix C.1 provide exterior crush and occupant compartment measurements, respectively.




Figure 5.12. Impact Side of Test Vehicle after Test 622421-01-1.



Figure 5.13. Rear Impact Side of Test Vehicle after Test 622421-01-1.



Figure 5.14. Overall Interior of Test Vehicle after Test 622421-01-1.



Figure 5.15. Interior of Test Vehicle on Impact Side after Test 622421-01-1.

Table 5.8. Occupant Compartment Deformation 622421-01-1.

Test Parameter	Specification (inches)	Measured (inches)
Roof	≤4.0	0.0
Windshield	≤3.0	0.0
A and B Pillars	≤5.0 overall/≤3.0 lateral	0.0
Foot Well/Toe Pan	≤9.0	5.3
Floor Pan/Transmission Tunnel	≤12.0	1.0
Side Front Panel	≤12.0	0.8
Front Door (above Seat)	≤9.0	0.0
Front Door (below Seat)	≤12.0	0.0

Table 5.9. Exterior Vehicle Damage 622421-01-1.

Test Parameter	Details
Side Windows	Remained intact
Maximum Exterior Deformation	20 inches at front bumper
VDS	01LFQ2
CDC	01FLEN2
Fuel Tank Damage	None
Description of Damage to Vehicle:	The bumper, grill, fender, and both headlights dislodged. The left front wheel bent, the tire ruptured, and one lug nut stud was dislodged. There were abrasions and deformities on the lower portion of the left doors. The exterior left front door panel pulled back one inch at the bottom. The exterior left rear door panel pulled back two inches at the bottom. There was a one-inch gap at the top of the left front and rear doors. The left rear wheel was deformed and the tire ruptured. The left taillight dislodged, and the rear bumper was deformed. The tail gate dislodged on the passenger side but remained attached on the driver's side.

5.7. OCCUPANT RISK FACTORS

Data from the accelerometers were digitized for evaluation of occupant risk, and the results are shown in Table 5.10. Figure C.7 in Appendix C.3 shows the vehicle angular displacements, and Figure C.8 through Figure C.10 in Appendix C.4 show acceleration versus time traces.

Table 5.10. Occupant Risk Factors for Test 622421-01-1.

Test Parameter	Specification ^a	Measured	Time
OIV, Longitudinal (ft/s)	≤ 40.0	18.7	0.1067 seconds on left side of interior
	≤ 30.0		
OIV, Lateral (ft/s)	≤ 40.0	18.2	0.1067 seconds on left side of interior
	≤ 30.0		
Ridedown, Longitudinal (g)	≤ 20.49	5.9	0.2474 - 0.2574 seconds
	≤ 15.0		
Ridedown, Lateral (g)	≤ 20.49	11.4	0.2874 - 0.2974 seconds
	≤ 15.0		
Theoretical Head Impact Velocity (THIV) (m/s)	N/A	7.7	0.1029 seconds on left side of interior
Acceleration Severity Index	N/A	1.5	0.0536 - 0.1036 seconds
50-ms Moving Avg. Accelerations (MA) Longitudinal (g)	N/A	-9.9	0.0366 - 0.0866 seconds
50-ms MA Lateral (g)	N/A	9.9	0.0310 - 0.0810 seconds
50-ms MA Vertical (g)	N/A	-3.4	0.2475 - 0.2975 seconds
Roll (°)	≤ 75	41.2	0.8913 seconds
Pitch (°)	≤ 75	17.2	0.8896 seconds
Yaw (°)	N/A	62.3	1.4843 seconds

^a Values in italics are the preferred MASH values

Note: N/A = Not Applicable

5.8. TEST SUMMARY

Figure 5.16 summarizes the results of MASH Test 622421-01-1.



GENERAL INFORMATION	
Test Agency:	Texas A&M Transportation Institute (TTI)
Test Standard/Test No.:	MASH 2016, Test 3-21
Project No.:	622421-01-1
Test Date:	6/25/2025
TEST ARTICLE	
Type:	Longitudinal Barrier
Name:	Free-standing-to-anchored F-shape PCB transition system
Length:	157 feet
Key Materials:	Galvanized ASTM A449, TxDOT Type D Asphalt, native soil, rebar grade 60, concrete barriers, galvanized anchor pins, and galvanized connection pins
Roadbase and Condition:	Type D Asphalt, damp
TEST VEHICLE	
Type/Designation:	2270P
Year, Make and Model:	2019 RAM 1500
Inertial Mass:	5006 lb
Dummy Mass:	N/A
Gross Static Mass:	5006 lb
IMPACT CONDITIONS	
Impact Speed:	63.0 mi/h
Impact Angle:	25.5°
Impact Location:	199.8 inches upstream from the centerline of the joint between barriers 9 and 10
Impact Severity:	123.1 kip-ft
EXIT CONDITIONS	
Exit Speed:	45.4 mi/h
Trajectory/Heading Angle:	11.9° / 16.6°
Exit Box Criteria:	
The vehicle met the exit box criteria	
Stopping Distance:	
178 ft downstream 27 ft to the impact side	
TEST ARTICLE DEFLECTIONS	
Dynamic:	30.4 inches
Permanent:	26.5 inches
Working Width:	51.3 inches
Working Width Height:	3.0 inches
VEHICLE DAMAGE	
VDS:	01LFQ2
CDC:	01FLEN2
Max Exterior Deformation:	20 inches at front bumper
Max Occupant Compartment Deformation:	5.3 inches in the foot well/toe pan
OCCUPANT RISK VALUES	
Longitudinal OIV:	18.7 ft/s
Lateral OIV:	18.2 ft/s
Longitudinal Ridedown:	5.9 g
Lateral Ridedown:	11.4 g
THIV:	7.7 m/s
ASI:	1.5
Max 50ms Longitudinal:	-9.9 g
Max 50ms Lateral:	9.9 g
Max 50ms Vertical:	-3.4 g
Max Roll:	41.2°
Max Pitch:	17.2°
Max Yaw:	62.3°





Figure 5.16. Summary of Results for MASH Test 3-21 on Free-Standing-to-Anchored F-shape PCB Transition system.

CHAPTER 6.

SUMMARY AND CONCLUSIONS

The crash test reported herein was performed on the free-standing-to-anchored F-shape PCB transition system in accordance with *MASH TEST 3-21*.

Table 6.1 shows that the free-standing-to-anchored F-shape PCB transition system met the performance criteria for *MASH TEST 3-21* for longitudinal barriers.

Table 6.1. Assessment Summary for *MASH TEST 3-21* Tests on free-standing-to-anchored PCB transition system.

Evaluation Criteria	Description ¹	Test 622421-01-1 (<i>MASH Test 3-21</i>)
A	Contain, Redirect, or Controlled Stop	S
D	No Penetration into Occupant Compartment	S
F	Roll and Pitch Limit	S
H	OIV Threshold	S
I	Ridedown Threshold	S
Overall	Evaluation	Pass

Note: S = Satisfactory; N/A = Not Applicable.

¹ See Table 3.2 for details

6.1. IMPLEMENTATION*

The optional *MASH Test 3-20*, involving a 2,420-lb small passenger car, was not considered critical for evaluating the transition system. Due to the lower vehicle mass, this test condition was not expected to produce higher impact loads on the transition system or

* The opinions/interpretations identified/expressed in this section of the report are outside the scope of TTI Proving Ground's A2LA Accreditation.

result in greater barrier deflections compared to the 5,000-lb pickup truck specified in *MASH* Test 3-21. Therefore, Test 3-20 was not conducted.


Based on the results of the crash testing presented herein, the free-standing-to-anchored F-shape PCB transition system is considered compliant with *MASH* Test Level 3 evaluation criteria.

REFERENCES


1. AASHTO. *Manual for Assessing Safety Hardware*, Second Edition. American Association of State Highway and Transportation Officials, Washington, DC, 2016.
2. Sheikh, N.M, and W.J., Schroeder. *Design and Testing of MSH TL-3 Compliant Anchored F-shape Portable Concrete Barrier System with Vertical Anchors*. Texas A&M Transportation Institute. Report 616811-01 1-4, College Station, Texas, 2025.


APPENDIX A.


DETAILS OF FREE-STANDING-TO-ANCHORED PCB TRANSITION SYSTEM





 Project #622421 PCB Anchored Transition	Roadside Safety and Physical Security Division - Proving Ground 2025-02-27
Drawn by GES	Scale 1:200
















	Roadside Safety and Physical Security Division - Proving Ground
Project #622421 PCB Anchored Transition	2025-02-27
Drawn by GES	Scale 1:10




Roadside Safety and
Physical Security Division -
Proving Ground

Project #622421 PCB Anchored Transition 2025-02-27

Drawn by GES Scale 1:10 Sheet 8 of 10 Rebar Bends






Texas A&M Transportation Institute	Roadside Safety and Physical Security Division - Proving Ground
Project #622421 PCB Anchored Transition	2025-02-27
Drawn by GES	Scale 1:5

Sheet 10 of 10 Assorted Parts

Connection Pin



1a. Pin is forged by Portland Bolt Company (Part #18241), with no welding, and galvanized per ASTM F2329 and A153.

1b. Material is ASTM A449.

	Roadside Safety and Physical Security Division - Proving Ground	
	Forged Connection Pin	2022-10-06
Drawn by GES	Scale 1:4	Sheet 1 of 1

APPENDIX B.

SUPPORTING CERTIFICATION DOCUMENTS

Concrete Core Test Report

Report Number: A117105-0333A

Service Date: 07/01/25

Report Date: 07/07/25

Task: 622421-01

Client

Texas Transportation Institute

Attn: Bill Griffith

TTI Business Office

3135 TAMU

College Station, TX 77843-3135

Project

Riverside Campus
Riverside Campus
Bryan, TX

Project Number: A1171057

Material Information

Specified Strength: 4000 psi @ 28 days

Specified Length:

Mix ID:

Nominal Maximum Size Aggregate:

Sample Information

Placement Date: 07/01/25

Sampled By:

Drill Directions: Vertical

Date Core Obtained: 07/01/25

Date Ends Trimmed: 07/01/25

Moisture Conditioning History: According to ASTM C-42

Laboratory Test Data

Core ID	Location	Cored Length (in)	Trim Length (in)	Capped Length (in)	Avg. Dia. (in)	Area (sq in)	Length / Diam. Ratio (in)	Max Load (lbs)	Corr. Factor	Comp. Strength (psi)	Fracture Strength (psi)	Density (pcf)
1	622421-01 A	12.65	8.00	8.22	4.01	12.63	2.05	73252	1.000	5800	3	6070
2	622421-01 B	10.64	5.78	6.10	4.01	12.63	1.52	79702	0.962	6070	3	6070

Comments:

Services:

Reported to:

Contractor:

Report Distribution:

(1) Texas Transportation Institute, Bill Griffith

(1) Texas Transportation Institute, Adam Meyer

Start/Stop:

Reviewed By:


Justin Mauss
Assistant Project Manager

Test Methods:

The tests were performed in general accordance with applicable ASTM, AASHTO, or DOT test methods. This report is exclusively for the use of the client indicated above and shall not be reproduced except in full without the written consent of our company. Test results transmitted herein are only applicable to the actual samples tested at the location(s) referenced and are not necessarily indicative of the properties of other apparently similar or identical materials.

C1004, 11/16/17, Rev. 5

Page 1 of 1



FOR TEXAS A&M TRANSPORTATION INST
PB INVOICE 159775
CUSTOMER PO 618141
EST. SHIP DATE 3/8/2023

Certificate of Conformance

We certify that the following items were manufactured and tested in accordance with the chemical, mechanical, dimensional and thread fit requirements of the specifications referenced.

1" X 29" DOMESTIC HOT-DIP GALVANIZED ASTM A449 BARRIER PIN WITH NO THREAD


HEAT	3083933		BASE STEEL	1045AR	DIAMETER	1	SOURCE	COMMERCIAL METALS CO					
C	MN	P	S	SI	NI	CR	MO	CU	PB	V	CB	N	
0.450	0.760	0.009	0.031	0.220	0.090	0.080	0.024	0.310	-	0.001	-	-	
TN					PROOF					HR			
81,580 LBF					51,500					269 HBN			
Lot#20863													

Coatings

- ITEMS HOT-DIP GALVANIZED PER ASTM F2329

Other

- ALL ITEMS MELTED & MANUFACTURED IN THE USA



Certification Department Quality Assurance
Dane McKinnon



Portland Bolt
& MANUFACTURING COMPANY
800-547-6758 | www.portlandbolt.com

sales@portlandbolt.com Phone: 800.547.6758 | Fax: 503.227.4634
www.portlandbolt.com 3441 NW Guam St. Portland OR, 97210

ORDER # 159775 rev. 1

DATE 2/17/2023

PAGE 1 of 1

SALESPERSON **Kyle Pettijohn**
DIRECT PHONE 800.628.9472

SOLD TO	SHIP TO	EMAIL
TEXAS A&M TRANSPORTATION INST TTI FINANCIAL SERVICES 3135 TAMU COLLEGE STATION, TX, 77843-3135 Phone: 979.317.2755 Fax: 979.227.7710	Adam Mayer @ 5126353115 TTI 3100 HWY 47 South BLDG 7091 Bryan, TX, 77807	kyle@portlandbolt.com
ATTN	Adam Mayer <a-mayer@tti.tamu.edu>	CUSTOMER PO 618141
SHIP DATE	3/8/2023 (scheduled)	SHIP VIA UPS Ground
LINE NUMBER	QTY. ORDERED	DESCRIPTION
1	18	1" x 29" domestic hot-dip galvanized ASTM A449 barrier pin with no thread



CERTIFIED MATERIAL TEST REPORT

Page 1 / 1

CUSTOMER SHIP TO		CUSTOMER BILL TO		GRADE	SHAPE / SIZE	DOCUMENT ID:
REGAL METALS INTERNATIONAL INC.		REGAL METALS INTERNATIONAL INC.		60 (420)	Rebar / #4 (13MM)	0001240440
207 SENTRY DR MANSFIELD, TX 76063-3609 USA		207 SENTRY DR MANSFIELD, TX 76063-3609 USA		LENGTH	WEIGHT	HEAT / BATCH
SALES ORDER 14902124/0000030		CUSTOMER MATERIAL N°		4000"	12,024 LB	58065018/02
CUSTOMER PURCHASE ORDER NUMBER Yard		BILL OF LADING 1327-03900622081		DATE	SPECIFICATION / DATE or REVISION ASTM A515/A515M-24	
				04/10/2025		

CHEMICAL COMPOSITION	C (%)	Mn (%)	P (%)	S (%)	Si (%)	Cr (%)	Ni (%)	Cr (%)	Mo (%)	Sn (%)	V (%)	Nb (%)	Al (%)	CIE99/A706
0.45	1.01	0.016	0.027	0.21	0.27	0.13	0.18	0.010	0.026	0.003	0.003	0.002	0.002	0.65
MECHANICAL PROPERTIES														
YS (PSI)	480	YS (MPa)	111350	UTS (PSI)	768	UTS (MPa)	8,000	Q/L (Inches)	8,000	Q/L (mm)	200,0	Blng. (%)	12.20	Bend Test OK
69650														
MECHANICAL PROPERTIES														
UTS /YS	1.60													

COMMENTS / NOTES

Gerdau's steel is 100% recyclable. Support the circular economy through our Metals Recycling Partnership. For details, visit www2.gerdau.com/metalrecycling or contact metalrecycling@gerdau.com.

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdau's possession. For all products other than billets or beam blanks, this material was Melted & Poured (via Electric Arc Furnace and Continuous Caster) and produced (Hot Rolled and, if applicable, Cold Drawn) in the U.S.A. For billets or beam blanks, this material was Melted & Poured (via Electric Arc Furnace and Continuous Caster) in the USA. CMTR complies with EN 10204 3.1.

Yashar BHASKAR YALAMANCHI, QUALITY DIRECTOR

Phone: (403) 267-1071 Email: Bhaskar.Yalamanchi@gerdau.com

Wade WADE LUMPKINS, QUALITY ASSURANCE MGR.

Phone: 972-779-3118 Email: Wade.Lumpkins@gerdau.com



CUSTOMER SHIP TO REGAL METALS INTERNATIONAL INC 207 SENTRY DR MANSFIELD, TX 76063-3609 USA SALES ORDER 14908124/010020	CUSTOMER BILL TO REGAL METALS INTERNATIONAL INC 207 SENTRY DR MANSFIELD, TX 76063-3609 USA		GRADE 60 (420) LENGTH 40'00"	SHAPE / SIZE Rebar / #5 (10MM) WEIGHT 23,781 LB	DOCUMENT ID: 0001237567 HEAT / BATCH 5912210102
	CUSTOMER MATERIAL N° 14908124/010020	CUSTOMER MATERIAL N° 14908124/010020			
CUSTOMER PURCHASE ORDER NUMBER 722687	BILL OF LADING 1327-4000621069	DATE 04/04/2025			

CHEMICAL COMPOSITION	Mn (%)	P (%)	S (%)	Si (%)	Cu (%)	Ni (%)	Cr (%)	Mo(%)	Sn (%)	V (%)	Nb (%)	Al (%)	Ceq/A706
0.44	0.89	0.019	0.029	0.23	0.25	0.11	0.23	0.031	0.009	0.028	0.002	0.002	0.62


MECHANICAL PROPERTIES	YS (MPa)	UTS (PSI)	UTS (MPa)	UTS (MPa)	G/L (inches)	G/L (mm)	Elong. (%)	Bend Test
539	539	10161	760	8,000		206,0	12,60	OK
UTS / YS 1.41								

MECHANICAL PROPERTIES
UTS / YS 1.41


COMMENTS / NOTES

Gerdaus steel is 100% recyclable. Support the circular economy through our Metals Recycling Partnership. For details, visit www2.gerdaus.com/metals-recycling, or contact metalsrecycling@gerdaus.com.

The above figures are certified chemical and physical test records as contained in the permanent records of the company. We certify that these data are correct and in compliance with specified requirements. No weld repair was performed on this material. The material has not been in contact with mercury while in Gerdaus' possession. For all products other than billets or beam blanks, this material was Melched & Poured via Electric Arc Furnace and Continuous Caster and produced (Hot Rolled and, if applicable, Cold Drawn) in the USA. For billets or beam blanks, this material was Melched & Poured (via Electric Arc Furnace and Continuous Caster) in the USA. CMTR complies with EN 10204 3.1.


BHASKAR VALAMANCHILI
QUALITY DIRECTOR
Phone: (401) 767-1071 Email: Shankar.Valamanchili@gerdaus.com

Phone: 972-770-3118 Email: Wade.Lompkins@gerdaus.com



United Machine Works

Craig Godwin, Inc. dba

Certificate of Conformance

To: SUMMIT PRECAST CONCRETE, LP
9930 INDUSTRIAL DR
Navasota, TX 77868
USA

From: United Machine Works
P O Box 525
New Waverly, TX 77358
USA

Packing List No: 145032
Shipping Date: 05/09/2025

Today's Date: 05/09/2025
PO Number: 25-108

CERTIFICATION DOCUMENTS

<u>PO Line No.</u>	<u>Number</u>	<u>Revision</u>	<u>Description</u>	<u>Job No.</u>	<u>Unit</u>	<u>Shipped</u>	<u>Ordered</u>	<u>Back Ordered</u>
1	241156 TTI ANCHOR PL		ANCHOR PLATE	72607	EA	21	21	0
	Serial No.		25-108-1-1, 25-108-1-2, 25-108-1-3, 25-108-1-4, 25-108-1-5					
	Serial No.		25-108-1-6, 25-108-1-7, 25-108-1-8, 25-108-1-9, 25-108-1-10					
	Serial No.		25-108-1-11, 25-108-1-12, 25-108-1-13, 25-108-1-14, 25-108-1-15					
	Serial No.		25-108-1-16, 25-108-1-17, 25-108-1-18, 25-108-1-19, 25-108-1-20					
	Serial No.		25-108-1-21					
			CERT ENVELOPE					

COUNTRY OF ORIGIN: USA

The materials, processes, and workmanship all conform to the requirements of all applicable specifications, drawings, and the purchase order supplied to Craig Godwin, Inc. dba. The appropriate documentation providing traceability is on file at Craig Godwin, Inc. dba. It is available for review by authorized customer representatives.

Authorized Signature
Craig Godwin, Inc. dba

Page 1 of 1



United
Machine
Works

Inspection Report

Purchase Order: 25-108			Date: 4/14/2025			Special Notes:						
Part Number: 241156 TTI ANCHOR PL			Revision:			Job# 72607						
Part Description: ANCHOR PLATE						Job # 3044						
Operators:			Inspector: <i>Kenway Baird</i>									
Specification			Measured Dimension of Serialized Parts									
Dimension	Tolerance	1	2	3	4	5	6	7	8	9	10	
Serial Number (if applicable)												
Heat Log Number			<i>UP4369</i>									
1	2-1/4"	±.125"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	
2	1-3/4"	±.125"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	
3	2-1/2"	±.125"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	
4	3-5/8"	±.125"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	
5	3-3/8"	±.125"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	
6	45°	±1/2°	45°	45°	45°	45°	45°	45°	45°	45°	45°	
7	R 1/2" TYP	±.125"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	
8	3"	±.125"	3"	3"	3"	3"	3"	3"	3"	3"	3"	
9	6"	±.125"	6"	6"	6"	6"	6"	6"	6"	6"	6"	
10	22-1/2"	±0 -1/4"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	
11	5-1/2"	±.125"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	
12	11/2"	±.125"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	
13												
14												
15	Verify Stamping, Etching, tags	Verified by	<i>AB</i>									
16	Final Inspection	Verified by QC Inspector	<i>AB</i>									
17												
18												
19												
20												
21												



United
Machine
Works

Inspection Report

Purchase Order: 25-108			Date: 4/14/2025			Special Notes:							
Part Number: 241156 TTI ANCHOR PL			Revision:			Job# 72607							
Part Description: ANCHOR PLATE													
Operators:			Inspector:										
Specification			Measured Dimension of Serialized Parts										
	Dimension	Tolerance	11	12	13	14	15	16	17	18	19	20	
	Serial Number (if applicable)												
	Heat Log Number		(0741369)										
1	2-1/4"	±.125"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	2 1/4"	
2	1-3/4"	±.125"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	
3	2-1/2"	±.125"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	
4	3-5/8"	±.125"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	3 5/8"	
5	3-3/8"	±.125"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	3 3/8"	
6	45°	±1/2°	45°	45°	45°	45°	45°	45°	45°	45°	45°	45°	
7	R 1/2" TYP	±.125"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	R 1/2"	
8	3"	±.125"	3"	3"	3"	3"	3"	3"	3"	3"	3"	3"	
9	6"	±.125"	6"	6"	6"	6"	6"	6"	6"	6"	6"	6"	
10	22-1/2"	+0 -1/4"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	22 1/2"	
11	5-1/2"	±.125"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	5 1/2"	
12	1/2"	±.125"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	
13													
14													
15	Verify Stamping, Etching tags	Verified by	AJD										
16	Final Inspection	Verified by QC Inspector	AJD										
17													
18													
19													
20													
21													



United
Machine
Works

Inspection Report

Purchase Order: 25-108			Date: 4/14/2025			Special Notes:		
Part Number: 241156 TTI ANCHOR PL			Revision:			Job# 72607		
Part Description: ANCHOR PLATE								
Operators:			Inspector:					
Item	Specification		Measured Dimension of Serialized Parts					
	Dimension	Tolerance	21					
	Serial Number (if applicable)							
	Heat Log Number							
1	2-1/4"	±.125"	2 1/4"					
2	1-3/4"	±.125"	1 3/4"					
3	2-1/2"	±.125"	2 1/2"					
4	3-5/8"	±.125"	3 5/8"					
5	3-3/8"	±.125"	3 3/8"					
6	45°	±1/2°	45°					
7	R 1/2" TYP	±.125"	1 1/2					
8	3"	±.125"	3"					
9	6"	±.125"	6"					
10	22-1/2"	+0 -1/4"	22 1/2"					
11	5-1/2"	±.125"	5 1/2"					
12	1/2"	±.125"	1/2"					
13								
14								
15	Verify Stamping, Etching, tags	Verified by	AJ					
16	Final Inspection	Verified by QC Inspector	AJ					
17								
18								
19								
20								
21								



UNI-FAB

CERTIFICATE OF MATERIAL

SPECIFICATIONS AND WORKMANSHIP

DATE: 5/7/25

PO# 143188

JOB: 72607

3044

PART NUMBER: 241156 TTI ANCHOR PL

PART DESCRIPTION:

ANCHOR PLATE

CUST PO: 25-108 LINE 1

S/N: TRACER 1 THRU 21

Material: A572GR50T1

HL: UF4369 /HT# KNA81

QUANTITY: 21

SPECIAL PROCESS: MANUFACTURED PER PRINT

COUNTRY OF ORIGIN: United States of America

The materials, processes, and workmanship all conform to the requirements of all applicable specifications, drawings, and the purchase order supplied to Uni-Fab. The appropriate documentation providing traceability is on file at Uni-Fab. It is available for review by authorized customer representatives.

KNA481	0,15	1,45	0,19	0,016	0,004	0,010	0,010	0,020	<0,005	0,039	0,002	0,036	0,002	<0,005	0,0000	0,0060	0,0002	0,0000	0,40	0,41	0,24
KNA485	0,15	1,48	0,21	0,011	0,003	0,010	0,010	0,010	<0,005	0,037	0,002	0,029	0,001	<0,005	0,0000	0,0090	0,0002	0,0000	0,40	0,40	0,23
KNA487	0,16	1,47	0,21	0,016	0,004	0,020	0,010	0,020	<0,005	0,038	0,002	0,027	0,002	<0,005	0,0000	0,0060	0,0002	0,0000	0,41	0,41	0,24
KNA488	0,16	1,47	0,20	0,017	0,007	0,020	0,010	0,010	<0,005	0,035	0,002	0,035	0,001	<0,005	0,0000	0,0070	0,0002	0,0000	0,41	0,41	0,24
KNA489	0,16	1,40	0,22	0,013	0,005	0,010	0,010	0,010	<0,005	0,041	0,002	0,033	0,001	<0,005	0,0000	0,0060	0,0002	0,0000	0,39	0,40	0,24
KNA490	0,16	1,47	0,21	0,011	0,003	0,020	0,010	0,010	<0,005	0,041	0,001	0,028	0,001	<0,005	0,0000	0,0100	0,0002	0,0000	0,41	0,41	0,24
KNA491	0,15	1,44	0,22	0,012	0,004	0,010	0,010	0,010	<0,005	0,043	0,002	0,030	0,001	<0,005	0,0000	0,0040	0,0002	0,0000	0,39	0,39	0,23

PROVA DI TRAZIONE TENSILE TEST		PROVA DI RESILIANZA IMPACT TEST - CHARPY V-NOTCH TEST		PROVA DI PIEGA BEND TEST		PROVA DI DUREZZA HARDNESS TEST		PROVA DI STRIZIONE Z% TEST	
C00	C01 LOCATOR POSITIONING (1)	C02 LOCATION POSIZIONE (2)	C03 TEST TESTING (3)	C04 ANGLE ANGOLILO (°)	C05 MANOMETRO MANOMETER [mm]	C06 PRESTAZIONE PERFORMANCE (3)	C07 RESULT TESTO (5)	C08 MEDIA MEAN VALUE	C09 2% VALORE MEDIO 2% MEAN VALUE
CAMPIONE SAMPLE				C41 NEGOZIO NEGOZIO (3)	C42 INDIVIDUAL INDIVIDUAL VALUES	C43 SINGOLI SINGULAR VALUES (3)	C44 INDIVIDUAL INDIVIDUAL VALUES	C45 INDIVIDUAL INDIVIDUAL VALUES (3)	C46 2% INDIVIDUAL 2% INDIVIDUAL VALUES
AS72GR50T1 Min 0.00 - 20.00				C10 SHAPE OF TEST PIECE PROFILO PROVINO (4)	C11 TEST TEST (3)	C12 DIREZIONE DIRECTION (3)	C13 LARGHEZZA WIDTH [mm]	C14 RINFORZO REINFORCE	C15 2% VALORE MEDIO 2% MEAN VALUE
AS72GR50T1 Max 0.00 - 20.00				C16 TEST TEST (3)	C17 TEST TEST (3)	C18 TEST TEST (3)	C19 TEST TEST (3)	C20 TEST TEST (3)	C21 TEST TEST (3)

GH761	12,70	2	P	T	20	399	517	34,6	P	10,00		P	0 00	0				
GH772	7,94	2	P	T	20	413	524	34,0	P	7,50		P	0 00	0				
GH776	9,53	2	P	T	20	412	525	33,2	P	7,50		P	0 00	0				
GH777	7,94	2	P	T	20	405	513	31,1	P	7,50		P	0 00	0				
GH784	7,94	2	P	T	20	422	520	32,6	P	7,50		P	0 00	0				
GH785	7,94	2	P	T	20	420	509	32,0	P	7,50		P	0 00	0				
GM791	7,94	2	P	T	20	398	507	33,3	P	7,50		P	0 00	0				
GH799	7,94	2	P	T	20	415	509	32,2	P	7,50		P	0 00	0				
GH802	9,53	2	P	T	20	392	519	31,6	P	7,50		P	0 00	0				
GH811	9,53	2	P	T	20	405	519	36,1	P	7,50		P	0 00	0				


ASME SA-370 FIG. 3 AND FIG. 10 / 11 - SAMPLE TAKEN AFTER PLATE HEAT TREATMENT

Z01						
ITEM	TOLLERANZA DI SPESORE TOLERANCE ON THICKNESS	TOLLERANZE DI LARGHEZZA TOLERANCE ON WIDTH	TOLLERANZE DI LUNGHEZZA TOLERANCE ON LENGTH	CONDIZIONI SUPERFICIALI SURFACE FINISH	PLANARITÀ FLATNESS	
13	ASTM A6/A6M	EN 10029	EN 10029	ASTM A6/A6M	ASTM A6/A6M	
15	ASTM A6/A6M	EN 10029	EN 10029	ASTM A6/A6M	ASTM A6/A6M	
16	ASTM A6/A6M	EN 10029	EN 10029	ASTM A6/A6M	ASTM A6/A6M	

Z06	Z07	Z08 ENTE COLLAUDO / INSPECTION BODY	Z02
Z07	PRODUCED FROM CONTINUOUS CAST SLAB AND HAVE A MINIMUM REDUCTION RATIO OF 3 TO 1. ACC. TO ASTM ED. 2022. FULLY KILLED, FINE GRAIN STEEL. Value of Mn maximum in derogation permitted up to 1.60%	TIMBRO DELL'ISPEttORE STAMP OF THE INSPECTION REPRESENTATIVE	METINVEST TRAMETAL S.p.A. F. Andrian CQ Manager


UF4369


Sale 23102423 - Order № 32304822 - Customer Order № WLY-36909 - DDT № 32322081 - Certificate № 597984 - 2/2



**Texas A&M
Transportation
Institute** Roadside Safety and
Physical Security Division -
Proving Ground
Project #822421 PCB Anchored Transition
Drawn by GES Scale 1:3 Sheet 7 of 8 Anchor Plate
2025-02-27
22-14822421-01 Barrier Drawing

S-Accreditation-17025-2017EIR-000 Project Files\622421-01 - Free-Standing to Anchored Barriers - Sheikh\Drafting, 622421-1\622421-01 Barrier Drawing





United Machine Works

Craig Godwin, Inc: dba

Certificate of Conformance

To: SUMMIT PRECAST CONCRETE, LP
9930 INDUSTRIAL DR
Navasota, TX 77868
USA

From: United Machine Works
P O Box 525
New Waverly, TX 77358
USA

Packing List No: 145031
Shipping Date: 05/09/2025


Today's Date: 05/09/2025
PO Number: 25-108

CERTIFICATION DOCUMENTS

<u>PO Line No.</u>	<u>Number</u>	<u>Revision</u>	<u>Description</u>	<u>Job No.</u>	<u>Unit</u>	<u>Shipped</u>	<u>Ordered</u>	<u>Back Ordered</u>
2	241156 TTI CON LOOP		CONNECTION LOOPS	72608	EA	35	35	0
	Serial No.		25-108-2-1, 25-108-2-2, 25-108-2-3, 25-108-2-4, 25-108-2-5					
	Serial No.		25-108-2-6, 25-108-2-7, 25-108-2-8, 25-108-2-9, 25-108-2-10					
	Serial No.		25-108-2-11, 25-108-2-12, 25-108-2-13, 25-108-2-14, 25-108-2-15					
	Serial No.		25-108-2-16, 25-108-2-17, 25-108-2-18, 25-108-2-19, 25-108-2-20					
	Serial No.		25-108-2-21, 25-108-2-22, 25-108-2-23, 25-108-2-24, 25-108-2-25					
	Serial No.		25-108-2-26, 25-108-2-27, 25-108-2-28, 25-108-2-29, 25-108-2-30					
	Serial No.		25-108-2-31, 25-108-2-32, 25-108-2-33, 25-108-2-34, 25-108-2-35					
			CERT ENVELOPE					

COUNTRY OF ORIGIN: USA

The materials, processes, and workmanship all conform to the requirements of all applicable specifications, drawings, and the purchase order supplied to Craig Godwin, Inc. dba. The appropriate documentation providing traceability is on file at Craig Godwin, Inc. dba. It is available for review by authorized customer representatives.



Authorized Signature
Craig Godwin, Inc. dba

Page 1 of 1



United
Machine
Works

Inspection Report

Purchase Order: 25-108		Date: 4/14/2025		Special Notes:							
Part Number: 241156 TTI CON LOOP		Revision:		Job# 72608							
Part Description: Connection Loop											
Operators:		Inspector: Steven Carter									
Specification		Measured Dimension of Serialized Parts									
Dimension	Tolerance	1	2	3	4	5	6	7	8	9	10
Serial Number (if applicable)		UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358
Heat Log Number		UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358
1	2"	±.125"	2"	2"	2"	2"	2"	2"	2"	2"	2"
2	3/4"	±.125"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
3	70 1/2"	±.125"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"
4	8"	±.125"	8"	8"	8"	8"	8"	8"	8"	8"	8"
5	45°	±1/2°	45°	45°	45°	45°	45°	45°	45°	45°	45°
6	24"	±.125"	24"	24"	24"	24"	24"	24"	24"	24"	24"
7	25 3/4"	±.125"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"
8											
9											
10											
11											
12											
13											
14											
15	Verify Stamping, Etching, tags	Verified by	AB								
16	Final Inspection	Verified by QC Inspector	AB								
17											
18											
19											
20											
21											



United
Machine
Works

Inspection Report

Purchase Order: 25-108		Date: 4/14/2025		Special Notes:							
Part Number: 241156 TTI CON LOOP		Revision:		Job# 72608							
Part Description: Connection Loop											
Operators:		Inspectors: Steven Carter									
Specification		Measured Dimension of Serialized Parts									
Dimension	Tolerance	11	12	13	14	15	16	17	18	19	20
Serial Number (If applicable)											
Heat Log Number		UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358
1	2"	±.125"	2"	2"	2"	2"	2"	2"	2"	2"	2"
2	Ø3/4"	±.125"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
3	70 1/2"	±.125"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"
4	8"	±.125"	8"	8"	8"	8"	8"	8"	8"	8"	8"
5	45°	±1/2°	45°	45°	45°	45°	45°	45°	45°	45°	45°
6	24"	±.125"	24"	24"	24"	24"	24"	24"	24"	24"	24"
7	25 3/4"	±.125"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"
8											
9											
10											
11											
12											
13											
14											
15	Verify Stamping, Etching tags	Verified by	AP								
16	Final Inspection	Verified by QC Inspector	AP								
17											
18											
19											
20											
21											



United
Machine
Works

Inspection Report

Purchase Order: 25-108		Date: 4/14/2025		Special Notes:							
Part Number: 241156 TTI CON LOOP		Revision:		Job# 72608							
Part Description: Connection Loop											
Operators:		Inspector: Steven Carter									
Specification			Measured Dimension of Serialized Parts								
Dimension	Tolerance	21	22	23	24	25	26	27	28	29	30
Serial Number (if applicable)		UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358
Heat Log Number		UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358	UF4358
1	2"	±.125"	2"	2"	2"	2"	2"	2"	2"	2"	2"
2	Ø3/4"	±.125"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
3	70-1/2"	±.125"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"
4	8"	±.125"	8"	8"	8"	8"	8"	8"	8"	8"	8"
5	45°	±1/2°	45°	45°	45°	45°	45°	45°	45°	45°	45°
6	24"	±.125"	24"	24"	24"	24"	24"	24"	24"	24"	24"
7	25-3/4"	±.125"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"
8											
9											
10											
11											
12											
13											
14											
15	Verify Stamping, Etching, tags	Verified by	AB								
16	Final Inspection	Verified by QC Inspector	AP								
17											
18											
19											
20											
21											



United
Machine
Works

Inspection Report

Purchase Order: 25-108			Date: 4/14/2025			Special Notes:		
Part Number: 241156 TTI CON LOOP			Revision:			Job# 72608		
Part Description: Connection Loop								
Operators:			Inspector: <i>Steven Carter</i>					
Dimension	Tolerance	Serial Number (If applicable)	Measured Dimension of Serialized Parts					
			31	32	33	34	35	36
1	2"	±.125"	2"	2"	2"	2"	2"	
2	Ø3/4"	±.125"	3/4"	3/4"	3/4"	3/4"	3/4"	
3	70 1/2"	±.125"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	70 1/2"	
4	8"	±.125"	8"	8"	8"	8"	8"	
5	45°	±1/2°	45°	45°	45°	45°	45°	
6	24"	±.125"	24"	24"	24"	24"	24"	
7	25-3/4"	±.125"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	25 3/4"	
8								
9								
10								
11								
12								
13								
14								
15	Verify Stamping, Etching, tags	Verified by	<i>WJS</i>			<i>WJS</i>		
16	Final Inspection	Verified by QC Inspector	<i>WJS</i>			<i>WJS</i>		
17								
18								
19								
20								
21								



UNI-FAB

CERTIFICATE OF MATERIAL

SPECIFICATIONS AND WORKMANSHIP

DATE: 5/7/25

PO# 143188

JOB: 72608

3044

PART NUMBER: 241156 TTI CON LOOP PART DESCRIPTION: CONNECTION LOOPS

CUST PO: 25-108 LINE 2

S/N: TRACER 1 THRU 35

Material: A572GR50T1


HL: UF4358 /HT# 3135487

QUANTITY: 35


SPECIAL PROCESS: MANUFACTURED PER PRINT

COUNTRY OF ORIGIN: United States of America

The materials, processes, and workmanship all conform to the requirements of all applicable specifications, drawings, and the purchase order supplied to Uni-Fab. The appropriate documentation providing traceability is on file at Uni-Fab. It is available for review by authorized customer representatives.



Roadside Safety and
Physical Security Division -
Proving Ground
Project #622421 PCB Anchored Transition
2025-02-27
Drawn by GES Scale 1:5 Sheet 8 of 8 Assorted Parts
S:\Accreditation-17025-2017\ER-000 Project Files\622421-01 - Free-Standing to Anchored Barrier - ShallowDrafting.622421-1622421-01 Barrier Drawing



Texas A&M
Transportation
Institute
 Roadside Safety and
 Physical Security Division -
 Proving Ground
 Project #622421 PCB Anchored Transition
 2025-02-27
 Drawn by GES Scale 1:5 Sheet 8 of 8 Assorted Parts
 S:\Accreditation-17025-2017\ER-000 Project Files\622421-01 - Free-Standing to Anchored Barriers - Sheikh\Drafting\622421-1\622421-01 Barrier Drawing



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Drew Fischer

Drew Fischer

Quality Assurance Manager

1SERIES-BPS®

LOT NO.: 3135487	S O'Neal Steel Inc	S O'Neal Steel	Delivery #: 86186875
CTION: ROUND 3/4 x 20'0" A36/52950	O	H	BOL#: 76450524
GRADE: ASTM A36-19/A529-19 Gr 50 RD	L 4530 MESSER AIRPORT HWY	I 4005 Grand Lakes Way	CUST PO#: 722129
ILL DATE: 12/15/2024	D BIRMINGHAM AL	P Grand Prairie TX	CUST P#: 834718
ILT DATE: 12/05/2024	US 35222-1927	US 75050-0000	DLVRY LBS / HEAT: 13698.000 LB
rt. No.: 86186875 / 135487A457	T 2055993000	T 9724027945	DLVRY PCS / HEAT: 456 EA
O	O	O	


Characteristic	Value	Characteristic	Value	Characteristic	Value
C 0.12%	Elongation Gage Lgth test 1 8IN				
Mn 0.91%	Reduction of Area test 1 64%				
P 0.005%	Yield to tensile ratio test1 0.71				
S 0.019%	Yield Strength test 2 55.8ksi				
Si 0.22%	Tensile Strength test 2 77.6ksi				
Cu 0.38%	Elongation test 2 42%				
Cr 0.10%	Elongation Gage Lgth test 2 2IN				
Ni 0.16%	Reduction of Area test 2 65%				
Mo 0.048%	Yield to tensile ratio test2 0.72				
V 0.000%	BHN @ Surface test 1 149BHN				
Cb 0.011%					
Sh 0.008%					
Al 0.000%					
N 0.0138%					
Carbon Eq F1554 0.30%	SUMMIT PRECAST CONCRETE				
Carbon Eq A529 0.38%	PO: 25-108				
Yield Strength test 1 55.0ksi	PART: 241156 TTI CON LOOP				
Tensile Strength test 1 77.6ksi	CONNECTION LOOPS				
Elongation test 1 27%					

The Following is true of the material represented by this MTR:
 *Material is fully killed and is Hot Rolled Steel
 *100% melted, rolled, and manufactured in the USA
 *EN10289:2004 3.1 compliant *Contains no weld repair
 *Contains no Mercury contamination
 *Manufactured in accordance with the latest version of the plant quality manual
 *Meets the "Buy America" requirements of 23 CFR 35.410, 49 CFR 681
 *Warning: This product can expose you to chemicals which are
 known to the State of California to cause cancer, birth defects or other
 reproductive harm. For more information go to www.P65Warnings.ca.gov
 *THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT
 STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE
 AS A FELONY UNDER FEDERAL STATUTE

RKS: ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
 I MEETS THE REQUIREMENTS OF F1554 GRADE 36 SUPPLEMENT S1

Lot 4358

Page 1 OF 1 03/17/2025 17:40:15



Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		69536		6:58	5/16/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N70130PMS				W3	9	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1518 lb	9472 lb	9560 lb	0.93%	4.00% M	44 gl	
1"LS	1635 lb	9967 lb	9900 lb	-0.67%	1.60% M	19 gl	
TYPE1/2	461 lb	2766 lb	2755 lb	-0.40%			
FLYASH	197 lb	1182 lb	1185 lb	0.25%			
WAT 1	24.8 gl	86.6 gl	86.0 gl	-0.65%		86.0 gl	
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			
VISO1000	10.00 /C	394.80 oz	396.00 oz	0.30%			

Actual	Num Batches:	1	Design	149.0 gl	Manual	6:58:32
Load	24147 lb	Design W/C: 0.315	Water/Cement: 0.316 T		Actual	148.7 gl
Slump:	4.00 in	Water in Truck: 0.0 gl	Adjust Water: 0.0 gl / Load	Trim Water: 0.0 gl / yd	To Add:	0.3 gl
Actual W/C Ratio: 0.315		Actual Water: 149 gl	Batched Cement: 3940 lb	Allowable Water: 0 lb		

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		69737		12:32	5/20/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N70130PMS				W3	64	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1518 lb	9472 lb	9380 lb	-0.97%	4.00% M	43 gl	
1"LS	1635 lb	9888 lb	9820 lb	-0.69%	0.80% M	9 gl	
TYPE1/2	461 lb	2766 lb	2755 lb	-0.40%			
FLYASH	197 lb	1182 lb	1185 lb	0.25%			
WAT 1	24.8 gl	96.0 gl	96.0 gl	0.02%		96.0 gl	
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			
VISO1000	10.00 /C	394.80 oz	395.00 oz	0.05%			

Actual	Num Batches:	1	Design W/C:	0.315	Water/Cement:	0.316 T	Design	149.0 gl	Actual	148.6 gl	Manual	12:32:51
Load	23971 lb		Water in Truck:	0.0 gl	Adjust Water:	0.0 gl	/ Load		0.0 gl	/ yd	To Add:	0.5 gl
Slump:	4.00 in						Trim Water:				Note:	Manual feed occured
Actual W/C Ratio:	0.315		Actual Water:	149 gl	Batched Cement:	3940 lb	Allowable Water:	1 lb				

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		69773		13:29	5/21/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N70130FMS				W3	29	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1343 lb	8380 lb	8360 lb	-0.24%	4.00% M	39 gl	
1"LS	1728 lb	10451 lb	10360 lb	-0.87%	0.80% M	10 gl	
TYPE1/2	461 lb	2766 lb	2760 lb	-0.22%			
FLYASH	197 lb	1182 lb	1190 lb	0.68%			
WAT 1	24.9 gl	100.7 gl	100.0 gl	-0.71%		100.0 gl	
VISO1000	10.00 /C	394.80 oz	394.00 oz	-0.20%			
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			

Actual	Load	23534 lb	Design W/C:	0.316	Water/Cement:	0.315 T	Design	149.3 gl	Actual	148.4 gl	Manual	13:29:51
Slump:	4.00 in		Water in Truck:	0.0 gl	Adjust Water:	0.0 gl / Load	Trim Water:	0.0 gl / yd			To Add:	0.9 gl
Actual W/C Ratio:	0.314		Actual Water:	148 gl	Batched Cement:	3950 lb	Allowable Water:	7 lb				

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		69862		13:29	5/22/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N70130FMS				W3	56	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1343 lb	8380 lb	8320 lb	-0.72%	4.00% M	38 gl	
1"LS	1728 lb	10430 lb	10340 lb	-0.86%	0.60% M	7 gl	
TYPE1/2	461 lb	2766 lb	2770 lb	0.14%			
FLYASH	197 lb	1182 lb	1190 lb	0.68%			
WAT 1	24.9 gl	103.1 gl	102.0 gl	* -1.05%		102.0 gl	
VISO1000	10.00 /C	394.80 oz	394.00 oz	-0.20%			
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			

Actual	Num Batches:	1	Design	149.2 gl	Actual	147.7 gl	Manual	13:29:56
Load	23501 lb	Design W/C: 0.315	Water/Cement: 0.314 T				To Add:	1.4 gl
Slump:	4.00 in	Water in Truck: 0.0 gl	Adjust Water: 0.0 gl / Load	Trim Water: 0.0 gl / yd			Note:	Manual feed occured
Actual W/C Ratio: 0.311		Actual Water: 148 gl	Batched Cement: 3960 lb	Allowable Water: 15 lb				

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		69975		9:17	5/27/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N70130FMS				W3	30	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1343 lb	8380 lb	8420 lb	0.47%	4.00% M	39 gl	
1"LS	1728 lb	10658 lb	10600 lb	-0.55%	2.80% M	35 gl	
TYPE1/2	461 lb	2766 lb	2760 lb	-0.22%			
FLYASH	197 lb	1182 lb	1185 lb	0.25%			
WAT 1	24.9 gl	75.7 gl	75.0 gl	-0.99%		75.0 gl	
VISO1000	10.00 /C	394.80 oz	395.00 oz	0.05%			
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			

Actual	Num Batches:	1	Design	149.2 gl	Actual	148.4 gl	Manual	9:17:25
Load	23621 lb	Design W/C: 0.315	Water/Cement: 0.316 T				To Add:	
Slump:	4.00 in	Water in Truck: 0.0 gl	Adjust Water: 0.0 gl / Load	Trim Water: 0.0 gl / yd				
Actual W/C Ratio: 0.314		Actual Water: 148 gl	Batched Cement: 3945 lb	Allowable Water: 5 lb				

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		70184		8:27	5/30/25
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.00 yd	N-N60130FMS				W3	17	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1516 lb	9514 lb	9480 lb	-0.36%	4.60% M	50 gl	
1"LS	1728 lb	10472 lb	10400 lb	-0.68%	1.00% M	12 gl	
WAT 1	23.0 gl	75.4 gl	75.0 gl	-0.58%			
TYPE1/2	395 lb	2370 lb	2370 lb	0.00%			
FLYASH	169 lb	1014 lb	1015 lb	0.10%			
VISO1000	10.00 /C	338.40 oz	338.00 oz	-0.12%			
PLASTIMENT	2.00 /C	67.68 oz	67.00 oz	-1.00%			

Actual	23916 lb	Design W/C	0.340	Water/Cement:	0.340	T	Design	138.0 gl	Actual	137.3 gl	Manual	8:27:05
Load		Slump:	4.00 in	Water in Truck:	0.0 gl	Adjust Water:	0.0 gl	/ Load	Trim Water:	0.0 gl	To Add:	0.7 gl
											Note:	Manual feed occured
Actual W/C Ratio:	0.339	Actual Water:	137 gl	Batched Cement:	3385 lb		Allowable Water:	6 lb				

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
		user		71053		9:08	6/16/25
Load	Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID
6.00	yd	N-N70130PMS				W3	26
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat
SAND	1471 lb	9223 lb	9300 lb	0.83%	4.50% M	48 gl	
1"LS	1667 lb	10102 lb	10020 lb	-0.81%	1.00% M	12 gl	
TYPE1/2	461 lb	2766 lb	2755 lb	-0.40%			
FLYASH	197 lb	1182 lb	1175 lb	*	-0.59%		
WAT 1	24.9 gl	89.6 gl	90.0 gl	0.47%		90.0 gl	
PLASTIMENT	2.00 /C	78.96 oz	79.00 oz	0.05%			
VIISO1000	10.00 /C	394.80 oz	396.00 oz	0.30%			

Actual	Num Batches:	1				Manual	9:08:17
Load	24031 lb	Design W/C	0.315	Water/Cement:	0.315 A	Design	149.2 gl
Slump:	4.00 in	Water in Truck:	0.0 gl	Adjust Water:	0.0 gl	/ Load	Trim Water:
Actual W/C Ratio:	0.315	Actual Water:	150 gl	Batched Cement:	3975 lb	Allowable Water:	2 lb
						To Add:	0.0 gl
						Note: Manual feed occurred	

APPENDIX C.

MASH TEST 3-21 (TEST 622421-01-1)

C.1. VEHICLE PROPERTIES AND INFORMATION



Date:	2025-06-25	Test No.:	622421-01-1	VIN No.:	1C6RR6GT7KS690392			
Year:	2019	Make:	RAM	Model:	1500			
Tire Size:	265/70 R 17	Tire Inflation Pressure:			35 psi			
Tread Type:	Highway	Odometer:			224576			
Note any damage to the vehicle prior to test: <u>None</u>								
<ul style="list-style-type: none"> • Denotes accelerometer location. 								
NOTES: <u>None</u>								
Engine Type:	V-8							
Engine CID:	5.7 liter							
Transmission Type:	<input checked="" type="checkbox"/> Auto or <input type="checkbox"/> Manual <input type="checkbox"/> FWD <input checked="" type="checkbox"/> RWD <input type="checkbox"/> 4WD							
Optional Equipment:	<u>None</u>							
Dummy Data:								
Type:								
Mass:								
Seat Position:								
Geometry: inches								
A	78.50	F	40.25	K	20.00			
B	74.00	G	28.25	L	30.00			
C	229.00	H	59.40	M	68.50			
D	48.25	I	11.75	N	68.00			
E	140.50	J	27.00	O	46.00			
Wheel Center Height Front	14.75	Wheel Well Clearance (Front)	6.00	Bottom Frame Height - Front	12.50			
Wheel Center Height Rear	14.75	Wheel Well Clearance (Rear)	9.25	Bottom Frame Height - Rear	22.50			
RANGE LIMIT: A=78 ±2 inches; C=237 ±13 inches; E=148 ±12 inches; F=39 ±3 inches; G = > 28 inches; H = 63 ±4 inches; O=43 ±4 inches, (M+N)/2=67 ±1.5 inches								
GVWR Ratings:		Mass: lb	Curb	Test Inertial	Gross Static			
Front	3700	M _{front}	2995	2890				
Back	3900	M _{rear}	2137	2116				
Total	6700	M _{Total}	5132	5006	5006			
(Allowable Range for TIM and GSM = 5000 lb ±110 lb)								
Mass Distribution:								
lb	LF:	1421	RF:	1469	LR:	1095	RR:	1021

Figure C.1. Vehicle Properties for Test 622421-01-1.

Date: 2025-06-25 Test No.: 622421-01-1 VIN No.: 1C6RR6GT7KS690392
 Year: 2019 Make: RAM Model: 1500

VEHICLE CRUSH MEASUREMENT SHEET¹

Complete When Applicable	
End Damage	Side Damage
Undeformed end width _____	Bowing: B1 _____ X1 _____
Corner shift: A1 _____ A2 _____	B2 _____ X2 _____
End shift at frame (CDC) (check one) < 4 inches _____ ≥ 4 inches _____	Bowing constant $\frac{X1 + X2}{2} = _____$

Note: Measure C₁ to C₆ from Driver to Passenger Side in Front or Rear Impacts – Rear to Front in Side Impacts.

Specific Impact Number	Plane* of C-Measurements	Direct Damage		Field L**	C ₁	C ₂	C ₃	C ₄	C ₅	C ₆	±D
		Width** (CDC)	Max*** Crush								
1	AT FRONT BUMPER	19	15	32	-	-	-	-	-	-	-14
2	SAME	19	20	50	-	-	-	-	-	-	67
	Measurements recorded										
	<input checked="" type="checkbox"/> inches or <input type="checkbox"/> mm										

¹Table taken from National Accident Sampling System (NASS).

*Identify the plane at which the C-measurements are taken (e.g., at bumper, above bumper, at sill, above sill, at beltline, etc.) or label adjustments (e.g., free space).

Free space value is defined as the distance between the baseline and the original body contour taken at the individual C locations. This may include the following: bumper lead, bumper taper, side protrusion, side taper, etc. Record the value for each C-measurement and maximum crush.




**Measure and document on the vehicle diagram the beginning or end of the direct damage width and field L (e.g., side damage with respect to undamaged axle).

***Measure and document on the vehicle diagram the location of the maximum crush.

Note: Use as many lines/columns as necessary to describe each damage profile.

Figure C.2. Exterior Crush Measurements for Test 622421-01-1.

Date: 2025-06-25 Test No.: 622421-01-1 VIN No.: 1C6RR6GT7KS690392
 Year: 2019 Make: RAM Model: 1500



*Lateral area across the cab from driver's side kickpanel to passenger's side kickpanel.

OCCUPANT COMPARTMENT DEFORMATION MEASUREMENT

	Before	After	Differ. (inches)
A1	65.00	65.00	0.00
A2	63.00	63.00	0.00
A3	65.50	65.50	0.00
B1	45.00	45.00	0.00
B2	38.00	38.00	0.00
B3	45.00	45.00	0.00
B4	39.50	39.50	0.00
B5	43.00	43.00	0.00
B6	39.50	39.50	0.00
C1	26.00	20.75	-5.25
C2	0.00	0.00	0.00
C3	26.00	26.00	0.00
D1	11.00	10.00	-1.00
D2	0.00	0.00	0.00
D3	11.50	11.50	0.00
E1	58.50	58.50	0.00
E2	63.50	63.75	0.25
E3	63.50	63.50	0.00
E4	63.50	63.75	0.25
F	59.00	59.00	0.00
G	59.00	59.00	0.00
H	37.50	37.50	0.00
I	37.50	37.50	0.00
J*	25.00	24.25	-0.75

Figure C.3. Occupant Compartment Measurements for Test 622421-01-1.

C.2. SEQUENTIAL PHOTOGRAPHS




Figure C.4. Sequential Photographs for Test 622421-01-1 (Overhead View).




Figure C.5. Sequential Photographs for Test 622421-01-1 (Downstream In-line View).






Figure C.6. Sequential Photographs for Test 622421-01-1 (Upstream Field Side Oblique View).

C.3. VEHICLE ANGULAR DISPLACEMENTS



Axes are vehicle-fixed.
Sequence for determining orientation:

1. Yaw.
2. Pitch.
3. Roll.



Test Number: 622421-01-1

Test Standard Test Number: *MASH* Test 3-21

Test Article: Free-standing-to-anchored PCB transition system

Test Vehicle: 2019 RAM 1500

Inertial Mass: 5006 lb

Gross Mass: 5006 lb

Impact Speed: 63.0 mi/h

Impact Angle: 25.5°

Figure C.7. Vehicle Angular Displacements for Test 622421-01-1.

C.4. VEHICLE ACCELERATIONS




Figure C.8. Vehicle Longitudinal Accelerometer Trace for Test 622421-01-1
(Accelerometer Located at Center of Gravity).




Figure C.9. Vehicle Lateral Accelerometer Trace for Test 622421-01-1
(Accelerometer Located at Center of Gravity).




Figure C.10. Vehicle Vertical Accelerometer Trace for Test 622421-01-1
(Accelerometer Located at Center of Gravity).

